

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



05400734457 Cold Shrink Insulator, 2/0awg *Minnesota Mining (3M)*

Catalog Number	05400734457
Manufacturer	Minnesota Mining (3M)
Description	3M™ Cold Shrink Connector Insulators 8420 and 8430 Series Are Designed Using 3M'S Proprietary Cold Shrink Delivery System. Products Are Supplied Prestretched On A Removable Core For Efficiency and Ease Of Installation. Removal Of The Core (Unwinding) After Positioning The Splice Allows The Product to Shrink Into Position Forming A Moisture-Tight Seal. The Live Memory Action Of The Specially Formulated Epdm Material Promotes A Permanent, Durable Environmental Seal and Insulation, With A Typical Operating Te
Weight per unit	
Product Category	Calicina 9 Terminating Vita
atures	
Cable Type	Power Cable
Number of Conductors	1
Shielding Type	Non-Shielded; Tape Shield; UniShield(R); Wire Shield
scriptions	
Description	COLDSHRINK INSULATOR 8426-9P,10/CASE
extra long description	3M 7000006132 3M™ Cold Shrink Conne
Features	Insulate secondary splices and submersible, dig-in and direct buried repairs easily with the quick-to-install 3M™ 8420 Cold Shrink Connector Insulator. This environmental sealing insulator installs without tools and retains its resiliency and pressure over time, providing moisture-tight sealing to protect your wires and cable splices from water damage. Use this tubular, open-ended sleeve to protect high-voltage air-insulated lugs and connectors and for environmental sealing of communications wires and oth
Long Description	3M™ Cold Shrink Connector Insulators 8420 and 8430 Series are designed using 3M's proprietary cold shrink delivery system. Products are supplied prestretched on a removable core for efficiency and ease of installation. Removal of the core (unwinding) after positioning the splice allows the product to shrink into position forming a moisture-tight seal. The live memory action of the specially formulated EPDM material promotes a permanent, durable environmental seal and insulation, with a typical operating te
	71



Carton

Weight Per each

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1 2.2 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information		
Brand	3M	
GTIN	00054007344575	
Manufacturers Part Number	700006132	
UPC	054007344575	
Taxonomies, Classifications, and C	ategories	
Category Description	HEAT/COLD SHRINK	
Туре	Cold Shrink Splice	
Packaging		