

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## **OSP10MW Occsen Pir SP/3W 120/277V GRD** *Eaton Wiring Devices*

Eaton Wiring Devices	
Catalog Number	0SP10MW
Manufacturer	Eaton Wiring Devices
Description	Occupancy Sensor, 20 A, 120/277 V, 3 W, 3.28 In Length, 1.40 In Width, 4.19 In Height, White, -4 °F Operating Temperature, +60 °C Operating Temperature
Weight per unit	N/A
Product Category	Lighting Occupancy Sensors
Features	
dimensions	4.6300 IN X 3.0000 IN X 2.1900 IN
load	LEDELVHALINCCFLMLVFLRElectrical motor loads
Mounting Type	Flush Mount
Poles	1
Descriptions	
Description	OCCSEN PIR SP/3W 120/277V GRD
extra long description	EWD OSP10M-W OccSen PIR SP/3W 120/2
Features	Enjoy advanced energy savings and state-of-the-art automation with Eaton's occupancy and vacancy sensors. Eaton's motion sensor lighting controls use advanced Passive Infrared (PIR) and ultrasonic sensing technology to detect your presence and switch lights ON. Then, once you've left the room, our sensors turn the lights OFF following a preset period of time. Sensors are the perfect solution for commercial and residential applications where a switch is inconveniently located and in spaces where lights may
Special Features	Decorator
Manufacturer Information	
Brand	COOPER WIRING DEVICES
GTIN	00032664729386
UPC	032664729386
Taxonomies, Classifications, and	d Categories
Category Description	Residential dimmers, motion sensors, controls, & photo cells
Туре	Occupancy sensor switch
Packaging	
Carton	6
Package	36

0

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
Mounting	FLUSH
standard	NOM,cULus Listed