

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

A ANY

0TS40 600V 40A 5 1/2X1 1/16 K5 Fuse Mersen Fuses

Catalog Number	0TS40
Manufacturer	Mersen Fuses
Description	Fuse Ots - Class K5 - Fast-Acting 600VAC 300VDC 40A Ferrule Amp-Trap®
Weight per unit	0.2300 (lbs/each)
Product Category	Renewable & Non-Renewable
Features	
AC Voltage Rating	600
amperage rating	
class	
connection	Ferrule
DC Voltage Rating	300
interrupt rating	
Voltage Rating	
Vaterial, Color, and Finish	
Body Material	PolyTube
Dimensions and Weight	
Size	5.5 x 1.06
	0.0 A 1.00
Descriptions	
Description	600V 40A 5 1/2X1 1/16 K5 FUSE Mersen OTS40 Fuse OTS - Class K5 -
extra long description Features	
	One-Time OTS general purpose fuses provide low cost protectio for feeder and branch-circuits serving lighting, heating, and othe non-motor loads. OTS fuses will safely interrupt available short circuit currents up to 50,000 amperes in all ratings. OTS fuses ar not rejection fuses and care should be taken to ensure that replacement fuses do not have lower interrupting ratings than original fuses.
Long Description	Fuse OTS - Class K5 - Fast-Acting 600VAC 300VDC 40A Ferrule Amp-Trap®
Product Type	Fuse Ots - Class K5 - Fast-Acting 600VAC 300VDC 40A Ferrule
Short Description	600V 40A 5 1/2x1 1/16 K5 FUSE
Special Features	Easy to read imprint label for quick recognition and replacement Low cost for high protection value



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Mersen
GTIN	00782001700768
Manufacturers Part Number	OTS40
UPC	782001700768
Taxonomies, Classifications, and Ca	ategories
Category Description	Fuses & Fuse Accessories
Туре	CLASS K5
Packaging	
Carton	1
Package	10
Weight Per each	0.23
Uses, Certifications, and Standards	
Application	Feeders Branch circuits Resistive heating Residential and small commercial installations
Mounting	Clip
standard	UL Listed to Standard 248-9 File E2137 CSA Certified to Standard C22.2 No. 248.9 (The Canadian Electrical Code requires these fuses in ratings 15 through 60A to be of the low melting point design use OTN 15-60.) Self-certified for DC per UL248