

- Receptacles will accept copper or aluminum wire
- Surface mount receptacles feature patented lay-in terminals that accept up to #4 AWG wire
- Surface mount receptacles allow wiring from back or bottom and feature concentric back knockouts plus an adjustable cord clamp
- Flush mount receptacles feature a heavy gauge galvanized steel mounting strap for corrosion resistance and fit in either 1- or 2-Gang enclosures
- “Universal” model plugs include blades for both 30A & 50A configurations of the same voltage
- Plug terminals feature pressure plates to protect wires



## Specific power device solutions for today's needs



### Remodel/retrofit solutions

Homes built prior to 1996 that haven't been re-wired will typically use 3-wire non-grounding connection points for ranges and dryers, which we support with a complete line of power devices.

See page B-38

Shown:  
32B



### Newer home solutions

Current code requires range & dryer applications to use 4-wire grounding connections. Homes built after 1996 usually have 4-wire grounding connection points for dryers & ranges.

See page B-40

Shown:  
S21



### Solutions for welders, generators and RVs

Power devices are also used by other equipment. Our broad offering includes 30A, 50A & 60A devices for specialty connection point needs.

See pages B-41 to B-44


Shown:  
1264



## Heavy duty grade power receptacles

### Product description

2-pole, 3-wire grounding  
30A, 125V/AC  
30A, 250V/AC



1263



1232



U1263

### Design features



- Heavy gauge galvanized steel mounting strap for corrosion resistance
- For use with copper or aluminum wire
- Flush receptacles fit one-gang or two-gang enclosures
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom

### Flush power receptacles

| Rating<br>A | V/AC | NEMA   | Description                                    | Color | Catalog no. |  |  |
|-------------|------|--------|--|-------|-------------|---|---|
| 30          | 125  | TT-30R | Flush mount power receptacle, matching plug 83 | BK    | □ 1263      | •   | •   |

Listed to UL498, file no. E15058; CSA certified to CSA C22.2, no. 42

### Flush power receptacles

| Rating<br>A | V/AC | NEMA  | Description                                     | Color | Catalog no. |  |  |
|-------------|------|-------|---|-------|-------------|---|---|
| 30          | 125  | 5-30R | Flush mount power receptacle, matching plug S41 | BK    | □ 1233      | •   | •   |
| 30          | 250  | 6-30R | Flush mount power receptacle, matching plug S42 | BK    | □ 1234      | •   | •   |

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

### Surface power receptacle

| Rating<br>A | V/AC | NEMA  | Description                                       | Color | Catalog no. |  |  |
|-------------|------|-------|---|-------|-------------|---|---|
| 30          | 250  | 6-30R | Surface mount power receptacle, matching plug S42 | BK    | □ 1232      | •   | •   |

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

### Panel power receptacles

| Rating<br>A | V/AC | NEMA   | Description                                    | Color | Catalog no. |  |  |
|-------------|------|--------|--|-------|-------------|---|---|
| 30          | 125  | TT-30R | Panel mount power receptacle, matching plug 83 | BK    | □ U1263     | •   | •   |

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

### Color ordering information:

BK (Black)



(Black)

**Dimensional information:** B-70 **Specification information:** Please visit [www.eaton.com/wiringdevices](http://www.eaton.com/wiringdevices)

**Compliances, specifications and availability are subject to change without notice.**


 Indicates NAFTA compliant - Page G-21

 RoHS compliant - Page G-21


### Standard size combination wallplates

#### Product description


3-Gang, 4-Gang




2 toggles & duplex receptacle




2 toggles & decorator




3 toggles & duplex receptacle




1-Gang  
1.59" hole




1-Gang  
2.15" hole



2-Gang  
2.15" hole



2-Gang  
2.28" hole



2-Gang  
2.47" hole

#### Combination 3-gang

| Description                             | Material                | Color suffix   | Catalog no. |   |   |
|---|-------------------------|----------------|-------------|---|---|
| 3-Gang<br>2 toggles & duplex receptacle | Nylon                   | B, GY, V, W    | □ 5158__    | • | • |
|   | Thermoset               | A, B, LA, V, W | □ 2158__    | • | • |
|   | 302/304 Stainless steel | —              | □ 93543     | • | • |
| 3-Gang<br>2 toggles & decorator         | Thermoset               | A, LA, V, W    | □ 2173__    | • | • |
|   | 302/304 Stainless steel | —              | □ 93443     | • | • |

#### Combination 4-gang

| Description                   | Material                | Color suffix | Catalog no. |   |   |
|-------------------------------|-------------------------|--------------|-------------|---|---|
| 4-Gang                        | Thermoset               | A, LA, V, W  | □ 2174__    | • | • |
| 3 toggles & duplex receptacle | 302/304 Stainless steel | —            | □ 93554     | • | • |

### Standard size power outlet wallplates

#### Product description

1-Gang, 2-Gang

#### Power outlet

| Description                     | Material                | Color suffix   | Catalog no. |   |   |
|---------------------------------|-------------------------|----------------|-------------|---|---|
| 1-Gang with 1.59" (40.5mm) hole | 302/304 Stainless steel | —              | □ 93111     | • | • |
| 1-Gang with 2.15" (54.8mm) hole | 302/304 Stainless steel | —              | □ 93221     | • | • |
| 2-Gang with 2.15" (54.8mm) hole | Thermoset               | A, B, LA, V, W | □ 2168__    | • | • |
|                                 | 302/304 Stainless steel | —              | □ 93227     | • | • |
| 2-Gang with 2.28" (57.9mm) hole | 302/304 Stainless steel | —              | □ 93228     | • | • |
| 2-Gang with 2.47" (62.7mm) hole | Nylon                   | V, W           | □ 5169__    | • | • |
|                                 | 302/304 Stainless steel | —              | □ 93223     | • | • |

### Standard size wallplate guide for power devices

#### Wallplates for power devices

| Power device catalog no.                           | Wallplate catalog no.    |
|--|--------------------------|
| 32B, 38B, 1233, 1234, 1253, 1254, 1257, 1258, 1263 | 2068, 2168, 93221, 93227 |

#### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), GY (Gray), LA (Light Almond), V (Ivory), W (White), Stainless Steel

|          |          |           |              |          |          |                   |
|----------|----------|-----------|--------------|----------|----------|-------------------|
| <b>A</b> | <b>B</b> | <b>GY</b> | <b>LA</b>    | <b>V</b> | <b>W</b> |                   |
| (Almond) | (Brown)  | (Gray)    | (Lt. Almond) | (Ivory)  | (White)  | (Stainless Steel) |

**Certification information:** 2000 and 5000 series wallplates are cULus certified; 93000 series wallplates are UL and CSA certified; 94000 are UL certified **Dimensional information:** C-5, C-6 **Specification information:** Please visit [www.eaton.com/wiringdevices](http://www.eaton.com/wiringdevices) **Compliances, specifications and availability are subject to change without notice.**

Indicates NAFTA compliant - Page G-21

RoHS compliant - Page G-21

- Receptacles will accept copper or aluminum wire
- Surface mount receptacles feature patented lay-in terminals that accept up to #4 AWG wire
- Surface mount receptacles allow wiring from back or bottom and feature concentric back knockouts plus an adjustable cord clamp
- Flush mount receptacles feature a heavy gauge galvanized steel mounting strap for corrosion resistance and fit in either 1- or 2-Gang enclosures
- “Universal” model plugs include blades for both 30A & 50A configurations of the same voltage
- Plug terminals feature pressure plates to protect wires



## Specific power device solutions for today's needs



### Remodel/retrofit solutions

Homes built prior to 1996 that haven't been re-wired will typically use 3-wire non-grounding connection points for ranges and dryers, which we support with a complete line of power devices.

See page B-38

Shown:  
32B



### Newer home solutions

Current code requires range & dryer applications to use 4-wire grounding connections. Homes built after 1996 usually have 4-wire grounding connection points for dryers & ranges.

See page B-40

Shown:  
S21



### Solutions for welders, generators and RVs

Power devices are also used by other equipment. Our broad offering includes 30A, 50A & 60A devices for specialty connection point needs.

See pages B-41 to B-44


Shown:  
1264



## Heavy duty grade power receptacles

### Product description

2-pole, 3-wire grounding  
 30A, 125V/AC  
 30A, 250V/AC



1263



1232



U1263

### Design features



- Heavy gauge galvanized steel mounting strap for corrosion resistance
- For use with copper or aluminum wire
- Flush receptacles fit one-gang or two-gang enclosures
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom

### Flush power receptacles

| Rating<br>A | V/AC | NEMA   | Description                                    | Color | Catalog no. |  |  |
|-------------|------|--------|--|-------|-------------|---|---|
| 30          | 125  | TT-30R | Flush mount power receptacle, matching plug 83 | BK    | □ 1263      | •   | •   |

Listed to UL498, file no. E15058; CSA certified to CSA C22.2, no. 42

### Flush power receptacles

| Rating<br>A | V/AC | NEMA  | Description                                     | Color | Catalog no. |  |  |
|-------------|------|-------|---|-------|-------------|---|---|
| 30          | 125  | 5-30R | Flush mount power receptacle, matching plug S41 | BK    | □ 1233      | •   | •   |
| 30          | 250  | 6-30R | Flush mount power receptacle, matching plug S42 | BK    | □ 1234      | •   | •   |

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

### Surface power receptacle

| Rating<br>A | V/AC | NEMA  | Description                                       | Color | Catalog no. |  |  |
|-------------|------|-------|---|-------|-------------|---|---|
| 30          | 250  | 6-30R | Surface mount power receptacle, matching plug S42 | BK    | □ 1232      | •   | •   |

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

### Panel power receptacles

| Rating<br>A | V/AC | NEMA   | Description                                    | Color | Catalog no. |  |  |
|-------------|------|--------|--|-------|-------------|---|---|
| 30          | 125  | TT-30R | Panel mount power receptacle, matching plug 83 | BK    | □ U1263     | •   | •   |

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

### Color ordering information:

BK (Black)



(Black)

**Dimensional information:** B-70 **Specification information:** Please visit [www.eaton.com/wiringdevices](http://www.eaton.com/wiringdevices)

**Compliances, specifications and availability are subject to change without notice.**


 Indicates NAFTA compliant - Page G-21

 RoHS compliant - Page G-21


### Standard size combination wallplates

#### Product description


3-Gang, 4-Gang




2 toggles & duplex receptacle




2 toggles & decorator




3 toggles & duplex receptacle




1-Gang  
1.59" hole




1-Gang  
2.15" hole



2-Gang  
2.15" hole



2-Gang  
2.28" hole



2-Gang  
2.47" hole

#### Combination 3-gang

| Description                             | Material                | Color suffix   | Catalog no. |   |   |
|---|-------------------------|----------------|-------------|---|---|
| 3-Gang<br>2 toggles & duplex receptacle | Nylon                   | B, GY, V, W    | □ 5158__    | • | • |
|   | Thermoset               | A, B, LA, V, W | □ 2158__    | • | • |
|   | 302/304 Stainless steel | —              | □ 93543     | • | • |
| 3-Gang<br>2 toggles & decorator         | Thermoset               | A, LA, V, W    | □ 2173__    | • | • |
|   | 302/304 Stainless steel | —              | □ 93443     | • | • |

#### Combination 4-gang

| Description                   | Material                | Color suffix | Catalog no. |   |   |
|-------------------------------|-------------------------|--------------|-------------|---|---|
| 4-Gang                        | Thermoset               | A, LA, V, W  | □ 2174__    | • | • |
| 3 toggles & duplex receptacle | 302/304 Stainless steel | —            | □ 93554     | • | • |

### Standard size power outlet wallplates

#### Product description

1-Gang, 2-Gang

#### Power outlet

| Description                     | Material                | Color suffix   | Catalog no. |   |   |
|---------------------------------|-------------------------|----------------|-------------|---|---|
| 1-Gang with 1.59" (40.5mm) hole | 302/304 Stainless steel | —              | □ 93111     | • | • |
| 1-Gang with 2.15" (54.8mm) hole | 302/304 Stainless steel | —              | □ 93221     | • | • |
| 2-Gang with 2.15" (54.8mm) hole | Thermoset               | A, B, LA, V, W | □ 2168__    | • | • |
|                                 | 302/304 Stainless steel | —              | □ 93227     | • | • |
| 2-Gang with 2.28" (57.9mm) hole | 302/304 Stainless steel | —              | □ 93228     | • | • |
| 2-Gang with 2.47" (62.7mm) hole | Nylon                   | V, W           | □ 5169__    | • | • |
|                                 | 302/304 Stainless steel | —              | □ 93223     | • | • |

### Standard size wallplate guide for power devices

#### Wallplates for power devices

| Power device catalog no.                           | Wallplate catalog no.    |
|--|--------------------------|
| 32B, 38B, 1233, 1234, 1253, 1254, 1257, 1258, 1263 | 2068, 2168, 93221, 93227 |

#### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), GY (Gray), LA (Light Almond), V (Ivory), W (White), Stainless Steel

|          |          |           |              |          |          |                   |
|----------|----------|-----------|--------------|----------|----------|-------------------|
| <b>A</b> | <b>B</b> | <b>GY</b> | <b>LA</b>    | <b>V</b> | <b>W</b> |                   |
| (Almond) | (Brown)  | (Gray)    | (Lt. Almond) | (Ivory)  | (White)  | (Stainless Steel) |

**Certification information:** 2000 and 5000 series wallplates are cULus certified; 93000 series wallplates are UL and CSA certified; 94000 are UL certified **Dimensional information:** C-5, C-6 **Specification information:** Please visit [www.eaton.com/wiringdevices](http://www.eaton.com/wiringdevices) **Compliances, specifications and availability are subject to change without notice.**

Indicates NAFTA compliant - Page G-21

RoHS compliant - Page G-21