


STRAIGHT BLADE RECEPTACLES

Tamper-Resistant Switch/GFCI Receptacles 15A, 125VAC



1595SWTTRWCC4


Features

- Protects children: patented shutter system helps prevent improper insertion of foreign objects.
- Meets National Electrical Code® Tamper-Resistant requirements.
- SafeLock™ Protection: if critical components are damaged and ground fault protection is lost, power to receptacle is disconnected.
- Up-down switching.
- 15 Amp single pole switch rated for 1/2 HP motor loads – perfect for bath or kitchen vents and garbage disposals.
- Feed-thru wiring configuration allows GFCI to protect downstream receptacles.
- Prevents line-load reversal miswire: no power to the face or downstream receptacles if wired incorrectly.
- Exceeds UL943 voltage surge requirements; survives 100x the required UL 3kA/6kV voltage surge test cycles.
- Trip indicator light (red LED).
- Two back wire holes per terminal.
- Side or internal screw-pressure-plate back wire with #10 – #14 AWG solid or stranded copper wire.
- Ground screw has a back wire clamp for easy installation.
- 10 kA short circuit rating.
- Mounting screws are shipped captive in the device and wall plate for easier installation.
- High-impact-resistant thermoplastic construction.
- Extra-long strap.
- Button colors match the device face.
- Dual-direction test and reset buttons.
- Class A rated GFCI.
- Supplied with matching TP26 nylon wall plate.
- Tri-drive screws.

Specifications

- Supply Voltage: 125VAC, 60 Hz
- Supply Voltage Range: 102-132 VAC
- Trip Threshold: 5± 1mA
- Trip Time: 0.025 sec., nominal per UL Standard
- 20 Amp feed-thru capacity

| CATALOG NUMBER | SWITCH RATING | | RECEPTACLE RATING | | COLOR | NEMA CONFIG. NO. | 3rd PARTY COMPLIANCE | | |
|---|---------------|-----|-------------------|-----|--------------|------------------|------------------------|-----------------------|--------------------------|
| | A. | VAC | A. | VAC | | | UL UL943 C22.2 No. 144 | UL UL498 C22.2 No. 42 | UL US UL20 C22.2 No. 111 |
| COMBINATION TAMPER-RESISTANT SINGLE POLE SWITCH/GFCI | | | | | | | | | |
| 1595SWTTRICC4 | 15 | 120 | 15 | 125 | Ivory | 5-15R | • | • | • |
| 1595SWTTRWCC4 | 15 | 120 | 15 | 125 | White | 5-15R | • | • | • |
| 1595SWTTRBKCC4 | 15 | 120 | 15 | 125 | Black | 5-15R | • | • | • |
| 1595SWTTRLACC4 | 15 | 120 | 15 | 125 | Light Almond | 5-15R | • | • | • |



DEVICES & WALL PLATES

Color Selection Chart

Devices & Plastic Wall Plate Colors



Ivory Light Almond White Green Antique Brass Dark Bronze Nickel



Black Blue Brown Gray Orange Red

See specific device and wall plate catalog charts for particular color availabilities.

Metal Wall Plates

Metal Finish



Aluminum Brass (Brushed) Polished Brass Stainless Steel Brushed Bronze Chrome

Custom Metal Wall Plates Paint Finish Colors

Paint Color



Orange Green Gray Yellow Glossy Black Brown White




Primer Red Pink Flat Black Ivory Light Almond Blue

To order custom metal wall plates, see Pages P-40 - P-44.

For additional colors consult factory.

STRAIGHT BLADE RECEPTACLES

Tamper-Resistant Switch/GFCI Receptacles 15A, 125VAC



1595SWTTRWCC4


Features

- Protects children: patented shutter system helps prevent improper insertion of foreign objects.
- Meets National Electrical Code® Tamper-Resistant requirements.
- SafeLock™ Protection: if critical components are damaged and ground fault protection is lost, power to receptacle is disconnected.
- Up-down switching.
- 15 Amp single pole switch rated for 1/2 HP motor loads – perfect for bath or kitchen vents and garbage disposals.
- Feed-thru wiring configuration allows GFCI to protect downstream receptacles.
- Prevents line-load reversal miswire: no power to the face or downstream receptacles if wired incorrectly.
- Exceeds UL943 voltage surge requirements; survives 100x the required UL 3kA/6kV voltage surge test cycles.
- Trip indicator light (red LED).
- Two back wire holes per terminal.
- Side or internal screw-pressure-plate back wire with #10 – #14 AWG solid or stranded copper wire.
- Ground screw has a back wire clamp for easy installation.
- 10 kA short circuit rating.
- Mounting screws are shipped captive in the device and wall plate for easier installation.
- High-impact-resistant thermoplastic construction.
- Extra-long strap.
- Button colors match the device face.
- Dual-direction test and reset buttons.
- Class A rated GFCI.
- Supplied with matching TP26 nylon wall plate.
- Tri-drive screws.

Specifications

- Supply Voltage: 125VAC, 60 Hz
- Supply Voltage Range: 102-132 VAC
- Trip Threshold: 5± 1mA
- Trip Time: 0.025 sec., nominal per UL Standard
- 20 Amp feed-thru capacity

| CATALOG NUMBER | SWITCH RATING | | RECEPTACLE RATING | | COLOR | NEMA CONFIG. NO. | 3rd PARTY COMPLIANCE | | |
|---|---------------|-----|-------------------|-----|--------------|------------------|------------------------|-----------------------|--------------------------|
| | A. | VAC | A. | VAC | | | UL UL943 C22.2 No. 144 | UL UL498 C22.2 No. 42 | UL US UL20 C22.2 No. 111 |
| COMBINATION TAMPER-RESISTANT SINGLE POLE SWITCH/GFCI | | | | | | | | | |
| 1595SWTTRICC4 | 15 | 120 | 15 | 125 | Ivory | 5-15R | • | • | • |
| 1595SWTTRWCC4 | 15 | 120 | 15 | 125 | White | 5-15R | • | • | • |
| 1595SWTTRBKCC4 | 15 | 120 | 15 | 125 | Black | 5-15R | • | • | • |
| 1595SWTTRLACC4 | 15 | 120 | 15 | 125 | Light Almond | 5-15R | • | • | • |



DEVICES & WALL PLATES

Color Selection Chart

Devices & Plastic Wall Plate Colors



Ivory Light Almond White Green Antique Brass Dark Bronze Nickel



Black Blue Brown Gray Orange Red

See specific device and wall plate catalog charts for particular color availabilities.

Metal Wall Plates

Metal Finish



Aluminum Brass (Brushed) Polished Brass Stainless Steel Brushed Bronze Chrome

Custom Metal Wall Plates Paint Finish Colors

Paint Color



Orange Green Gray Yellow Glossy Black Brown White



Primer Red Pink Flat Black Ivory Light Almond Blue

To order custom metal wall plates, see Pages P-40 - P-44.

For additional colors consult factory.