

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



# **15W33 Straight Blade IP67 Conn 20A 125V 5-20R** Pass & Seymour/Legrand

Catalog Number	15W33
Manufacturer	Pass & Seymour/Legrand
Description	Rated Watertight For 1, 500 Psi High-Pressure Hosedown, Pass and Seymour Plugs and Connectors Feature Multiple Seals to Ensure Protection Against The Environment. Constructed Of A Sturdy Rubber Body, Which Makes Them Impact- and Chemical-Resistant, They Have Nickel-Plated Blades and Contacts For Superior Corrosion Resistance.
Weight per unit	0.4375 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out
Features	
amperage rating	20
Material	Rubber
Number of Wires	3.0
Poles	2
Voltage Rating	
Wire Size	14 - 12 AWG
Material, Color, and Finish	
Color	Yellow
<b>Dimensions and Weight</b>	
Size	4.75"
Descriptions	
Description	STRAIGHT BLADE IP67 CONN 20A 125V 5-20R
extra long description	P&S 15W33 STR BLADE IP67 CONN 20A 1
Long Description	Rated watertight for 1,500 psi high-pressure hosedown, Pass and
	Seymour plugs and connectors feature multiple seals to ensure protection against the environment. Constructed of a sturdy rubber body, which makes them impact- and chemical-resistant, they have nickel-plated blades and contacts for superior corrosion resistance.
Product Type	STR Blade IP67 Conn 20A 125V 5-20R
Special Features	Quick drive assembly screws, floating blades, rubber body construction, multiple ring seals



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

NASSI	ufacture	r Intor	MATIAN
IVIALII	11411111		1114111111
IVIGII	aiustais		HILLIOII

Brand	Pass and Seymour	
GTIN	00785007114324	
Manufacturers Part Number	15W-33	
UPC	785007114324	

## **Taxonomies, Classifications, and Categories**

Category Description	Industrial cord connectors
Туре	Watertight Connector

#### **Trade Size**

Amperage 20.0

### **Packaging**

Carton	1	
Package	10	
Weight Per each	0.4375	

## Uses, Certifications, and Standards

Application	Commercial
nema rating	5-20R
standard	UL, UL 498