

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



160DC 4" Watertight Hub *Bridgeport Fittings*

Catalog Number	160DC
Manufacturer	Bridgeport Fittings
Description	Threaded Hub, Zinc Die Cast, Size 4 Inch
Weight per unit	3.4 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

Cable Entry	Through Rigid conduit into throat of fitting
Material	Zinc Die Cast
modia	Voc

Material, Color, and Finish

Finish Bal	المريسية والم
------------	---------------

Dimensions and Weight

Size	4
JILO	

Descriptions

Description	4" WATERTIGHT HUB
extra long description	BPT 160-DC 4" THREADED HUB
Long Description	Threaded Hub, Zinc Die Cast, Size 4 Inch
Product Type	4" Threaded Hub
Special Features	UL Type 4 Water Tight

Manufacturer Information

Brand	Bridgeport
GTIN	00781747091604
Manufacturers Part Number	160-DC
UPC	781747091604

Taxonomies, Classifications, and Categories

Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS
	AND THREADLESS CONNECTOR
Туре	Threaded Hubs
Trade Size	
Trade Size	4

Packaging

<i>y</i>	
Carton	1
Package	5
Weight Per each	



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

cs, cei tirications, and stand	idi us
Application	To secure threaded rigid service entrance conduit to box or enclosure. Insulated throat rated 105 degree c. UL listed Type 4 -
	enclosure. Insulated throat rated 105 degree c. Of listed Type 4 -
	Watertightnants from entering enclosure. Suitable for Aluminum
	and Steel Rigid Conduit
standard	UL, CSA
Temperature Rating	105 C
-	