


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Packaging

Carton

Weight Per each

162 Fuse Reducer 1 PR 100 *Mersen Fuses*

Catalog Number	162
Manufacturer	Mersen Fuses
Description	Mersen Fuse Reducers Allow The Use Of Lower Rated Fuses In Existing Equipment Having Clips With Higher Ampere Ratings. The Use Of Closer Rated Time-Delay Fuses Can Improve Circuit Protection. For Example, Renewable or One-Time Fuses Feeding A Motor Can Be Replaced With Fuses Sized Closer to The Motor Nameplate Current. Non-Rejection Reducers Will Allow Class H, or R Fuses to Fit Class H or K Clips. Rejection-Type Reducers Will Allow Only Class R Fuses to Fit Class R Clips or Only Class J Fuses to Fit C
Weight per unit	0.0300 (lbs/each)
Product Category	Clips, Redcrs, Rejctrs, Etc.
eatures	
class	H & K
Voltage Rating	600
Descriptions	
Description	FUSE REDUCER 1 PR 100
extra long description	FERRAZ 162 100-60A FUSE REDUCER PR
Long Description	Mersen fuse reducers allow the use of lower rated fuses in existing equipment—having clips with higher ampere ratings. Th use of closer rated time-delay fuses can improve circuit protection. For example, renewable or one-time fuses feeding a motor can be replaced with fuses sized closer to the motor nameplate current. Non-rejection reducers will allow Class H, K or R fuses to fit Class H or K clips. Rejection-type reducers will allow only Class R fuses to fit Class R clips or only Class J fuses to fit C
Product Type	Fuse Reducer 100-60A 250V
/lanufacturer Information	
Brand	Mersen Fuses
GTIN	00782001752255
UPC	782001752255
axonomies, Classifications, and	Categories
Туре	<u> </u>

1

0.03



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Application	Mersen fuse reducers allow the use of lower rated fuses in existing equipment—having clips with higher ampere ratings. The use of closer rated time-delay fuses can improve circuit protection. For example, renewable or one-time fuses feeding a motor can be replaced with fuses sized closer to the motor nameplate current. Non-rejection reducers will allow Class H, K or R fuses to fit Class H or K clips. Rejection-type reducers will allow only Class R fuses to fit Class R clips or only Class J fuses to fit C
standard	250V and 600V Class H, K, and R - UL Listed Guide No. IZZR, CSA Certified. 600V Class J - UL Listed Guide No. IZZR, CSA Certified 30-600A