



PRODUCT DATA SHEET

Upside Down Marking Paints-Safety Red, 17 Wt Oz
 No. 18200 | Item# 1005216 | Case# 1005215



Product Description	Clearly and effectively marks the location of underground utilities. Colors meet the A.P.W.A. One Call International Color Standards. Safe to use on turf grass, fields, and golf courses.
Color	Safety Red
Applications	To identify and code surfaces such as metal, concrete, asphalt, gravel, soil, trees and grass for construction, utility, recreational, municipal and landscaping sites, golf courses, nurseries and surveying.
Unit Package Description	20 Ounce Aerosol
Brand	CRC
Generic Description 1	Upside Down Marking Paints
Net Fill	17 Wt Oz
UPC Code	078254182001
Unit Dimensions	9.25H x 2.63W x 2.63D in
Units Per Case	6
Case Dimensions	10H x 5.75W x 8.25D in
Cases Per Pallet	120
Case Weight	8 lbs
1 2 of 5 Code	30078254182002
Appearance	Red Liquid
Flash point (F)	-2°F
Flash point (C)	-19°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.77 to 0.85
Plastic Safe	Yes
Dry Time - Fully Dry	1 Hour
Dry Time - Tack Free	30 Minutes
Coverage	0 to 700 Linear Feet
Propellant	Hydrocarbon

Last revised: 3/27/2018
 Page 1 of 2



Customer Care: 800-556-5074
 Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET

Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	51.7
VOC g/L (Consumer Product def)	526.7
VOC lbs/gal (Consumer Prod def)	4.4
VOC Category	Aerosol Coating: Ground Traffic/Marking
MIR Limit (EPA)	1.2
MIR Limit (CA)	0.85
MIR Value	0.58
Removal (How To)	Remove: WET paint with mineral spirits or turpentine, DRY paint with lacquer thinner/stripner.



Last revised: 3/27/2018
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.