



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Upside Down Marking Paints - Alert Orange

**Other means of identification**

**Product code** 18204

**Recommended use** Coating

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service** 800-272-4620

**24-Hour Emergency (CHEMTREC)** 800-424-9300 (US)

703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
Gases under pressure Liquefied gas

**Health hazards** Carcinogenicity Category 2  
Aspiration hazard Category 1

**Environmental hazards** Hazardous to the aquatic environment, long-term hazard Category 3

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Suspected of causing cancer.

**Precautionary statement**

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If swallowed: Call a physician/poison center immediately. Do NOT induce vomiting. If exposed or concerned: Get medical attention.

**Storage** Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose or store at temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

**Hazard(s) not otherwise classified (HNOC)** Harmful to aquatic life with long lasting effects.

**Supplemental information**

53.89% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

### 3. Composition/information on ingredients

---

#### Mixtures

| Chemical name                               | Common name and synonyms | CAS number | %       |
|---|--------------------------|------------|---------|
| Water                                       |                          | 7732-18-5  | 20 - 30 |
| Calcium carbonate                           |                          | 1317-65-3  | 10 - 20 |
| n-Butane                                    |                          | 106-97-8   | 10 - 20 |
| Propane                                     |                          | 74-98-6    | 10 - 20 |
| Solvent naphtha (petroleum), light aliph.   |                          | 64742-89-8 | 10 - 20 |
| Distillates (petroleum), hydrotreated light |                          | 64742-47-8 | 1 - 5   |
| Titanium dioxide                            |                          | 13463-67-7 | < 1     |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

---

|   |  |
|---|--|
| <b>Inhalation</b>   | Move to fresh air. Call a physician if symptoms develop or persist.  |
| <b>Skin contact</b>   | Wash off with soap and water. Take off contaminated clothing and wash before reuse. Get medical attention if irritation develops and persists.   |
| <b>Eye contact</b>  | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.   |
| <b>Ingestion</b>  | Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis. |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Direct contact with eyes may cause temporary irritation.   |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically.   |
| <b>General information</b>  | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.   |

#### 5. Fire-fighting measures

---

|  |  |
|--|--|
| <b>Suitable extinguishing media</b>                                  | Small Fires: Powder. Water spray. Carbon dioxide (CO2). Dry sand.<br><br>Large Fires: Water spray. Alcohol resistant foam.   |
| <b>Unsuitable extinguishing media</b>                                | None known.  |
| <b>Specific hazards arising from the chemical</b>                    | Contents under pressure. Pressurized container may explode when exposed to heat or flame.  |
| <b>Special protective equipment and precautions for firefighters</b> | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.   |
| <b>Fire-fighting equipment/instructions</b>                          | In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| <b>General fire hazards</b>  | Extremely flammable aerosol.   |

#### 6. Accidental release measures

---

|  |  |
|--|--|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.   |
| <b>Methods and materials for containment and cleaning up</b>               | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. |
| <b>Environmental precautions</b>   | Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.   |

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

### Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Store in a well-ventilated place. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                        | Type | Value      | Form                 |
|-----------------------------------|------|------------|----------------------|
| Calcium carbonate (CAS 1317-65-3) | PEL  | 5 mg/m3    | Respirable fraction. |
| Propane (CAS 74-98-6)             | PEL  | 15 mg/m3   | Total dust.          |
|                                   |      | 1800 mg/m3 |                      |
| Titanium dioxide (CAS 13463-67-7) | PEL  | 1000 ppm   | Total dust.          |
|                                   |      | 15 mg/m3   |                      |

#### US. ACGIH Threshold Limit Values

| Components                        | Type | Value    |
|-----------------------------------|------|----------|
| n-Butane (CAS 106-97-8)           | STEL | 1000 ppm |
| Titanium dioxide (CAS 13463-67-7) | TWA  | 10 mg/m3 |

#### US. NIOSH: Pocket Guide to Chemical Hazards

| Components   | Type | Value      | Form        |
|--|------|------------|-------------|
| Calcium carbonate (CAS 1317-65-3)                            | TWA  | 5 mg/m3    | Respirable. |
| Distillates (petroleum), hydrotreated light (CAS 64742-47-8) | TWA  | 10 mg/m3   | Total       |
|  |      | 100 mg/m3  |             |
| n-Butane (CAS 106-97-8)                                      | TWA  | 1900 mg/m3 |             |
|  |      | 800 ppm    |             |
| Propane (CAS 74-98-6)  | TWA  | 1800 mg/m3 |             |
|  |      | 1000 ppm   |             |

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin protection

##### Hand protection

Wear protective gloves such as nitrile or rubber.

##### Other

Wear appropriate chemical resistant clothing.

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Air monitoring is needed to determine actual employee exposure levels.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

Material name: Upside Down Marking Paints - Alert Orange

1055 Version #: 01 Issue date: 10-01-2013

SDS US

3 / 8

|   |                           |
|---|---------------------------|
| <b>Physical state</b>                               | Liquid.                   |
| <b>Form</b>   | Aerosol.                  |
| <b>Color</b>  | Orange.                   |
| <b>Odor</b>   | Aromatic.                 |
| <b>Odor threshold</b>                               | Not available.            |
| <b>pH</b>   | Not available.            |
| <b>Melting point/freezing point</b>                 | -138.8 °F (-94.9 °C)      |
| <b>Initial boiling point and boiling range</b>      | -47.2 °F (-44 °C)         |
| <b>Flash point</b>                                  | -2.2 °F (-19 °C)          |
| <b>Evaporation rate</b>                             | Not available.            |
| <b>Flammability (solid, gas)</b>                    | Not available.            |
| <b>Upper/lower flammability or explosive limits</b> |                           |
| <b>Flammability limit - lower (%)</b>               | 1.5 %                     |
| <b>Flammability limit - upper (%)</b>               | 10.9 %                    |
| <b>Vapor pressure</b>                               | 2221.9 hPa estimated      |
| <b>Vapor density</b>                                | > 1 (air = 1)             |
| <b>Relative density</b>                             | 0.77 - 0.85               |
| <b>Solubility (water)</b>                           | Not available.            |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.            |
| <b>Auto-ignition temperature</b>                    | 410 °F (210 °C) estimated |
| <b>Decomposition temperature</b>                    | Not available.            |
| <b>Viscosity (kinematic)</b>                        | Not available.            |
| <b>Percent volatile</b>                             | 75 %                      |

## 10. Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.   |
| <b>Possibility of hazardous reactions</b> | No dangerous reaction known under conditions of normal use.                                   |
| <b>Conditions to avoid</b>                | Heat, flames and sparks. Contact with incompatible materials.                                 |
| <b>Incompatible materials</b>             | Strong oxidizing agents. Acids. Fluorine. Chlorine. Nitrates.                                 |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.  |

## 11. Toxicological information

### Information on likely routes of exposure

|   |  |
|---|--|
| <b>Ingestion</b>  | May be fatal if swallowed and enters airways.            |
| <b>Inhalation</b>   | Prolonged inhalation may be harmful.                     |
| <b>Skin contact</b>   | Prolonged skin contact may cause temporary irritation.   |
| <b>Eye contact</b>  | Direct contact with eyes may cause temporary irritation. |
| <b>Symptoms related to the physical, chemical and toxicological characteristics</b> | Direct contact with eyes may cause temporary irritation. |

### Information on toxicological effects

|                       |   |
|-----------------------|---|
| <b>Acute toxicity</b> | May be fatal if swallowed and enters airways. |
|-----------------------|---|

| <b>Product</b>                            | <b>Species</b> | <b>Test Results</b>                  |
|---|----------------|--------------------------------------|
| Upside Down Marking Paints - Alert Orange |                |                                      |
| <b>Acute</b>                              |                |                                      |
| <i>Dermal</i>                             |                |                                      |
| LD50                                      | Rabbit         | 25990.8555 mg/kg estimated           |
| <i>Inhalation</i>                         |                |                                      |
| LC50                                      | Rat            | 8179.4048 mg/l, 15 Minutes estimated |

| Product   | Species  | Test Results                        |
|---|--|-------------------------------------|
|   |  | 6351.3516 mg/l, 4 hours estimated   |
| <i>Oral</i><br>LD50   | Rat  | 90459.0625 mg/kg estimated          |
| <b>Chronic</b><br><i>Oral</i><br>LD50                         | Mouse  | 2626.2632 g/kg estimated            |
| <b>Skin corrosion/irritation</b>                              | Prolonged skin contact may cause temporary irritation.   |                                     |
| <b>Serious eye damage/eye irritation</b>                      | Direct contact with eyes may cause temporary irritation.   |                                     |
| <b>Respiratory sensitization</b>                              | Not available.   |                                     |
| <b>Skin sensitization</b>                                     | This product is not expected to cause skin sensitization.  |                                     |
| <b>Germ cell mutagenicity</b>                                 | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |                                     |
| <b>Carcinogenicity</b>  | Suspected of causing cancer.   |                                     |
| <b>IARC Monographs. Overall Evaluation of Carcinogenicity</b> |  |                                     |
| Titanium dioxide (CAS 13463-67-7)                             |  | 2B Possibly carcinogenic to humans. |
| <b>Reproductive toxicity</b>                                  | This product is not expected to cause reproductive or developmental effects.                                     |                                     |
| <b>Specific target organ toxicity - single exposure</b>       | Not classified.  |                                     |
| <b>Specific target organ toxicity - repeated exposure</b>     | Not classified.  |                                     |
| <b>Aspiration hazard</b>                                      | May be fatal if swallowed and enters airways.  |                                     |
| <b>Chronic effects</b>  | Prolonged inhalation may be harmful.   |                                     |

## 12. Ecological information

|  |   |   |                                     |
|--|---|---|-------------------------------------|
| <b>Ecotoxicity</b>   | Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.   |   |                                     |
| <b>Product</b>   | <b>Species</b>  | <b>Test Results</b>                           |                                     |
| Upside Down Marking Paints - Alert Orange                    |   |   |                                     |
| <i>Acute</i>   |   |   |                                     |
| Crustacea  | EC50  | Daphnia                                       | 9545.4541 mg/l, 48 hours estimated  |
| Fish   | LC50  | Fish  | 15568.5059 mg/l, 96 hours estimated |
| <b>Components</b>  | <b>Species</b>  | <b>Test Results</b>                           |                                     |
| Distillates (petroleum), hydrotreated light (CAS 64742-47-8) |   |   |                                     |
| <i>Acute</i>   |   |   |                                     |
|  | EC50  | Invertebrate (saltwater)                      | 4720 mg/l, 96 hours                 |
| <b>Aquatic</b>   |   |   |                                     |
| <i>Acute</i>   |   |   |                                     |
| Fish   | LC50  | Bluegill ( <i>Lepomis macrochirus</i> )       | 1740 mg/l, 96 hours                 |
|  |   | Fathead minnow ( <i>Pimephales promelas</i> ) | 45 mg/l, 96 hours                   |
| Titanium dioxide (CAS 13463-67-7)                            |   |   |                                     |
| <b>Aquatic</b>   |   |   |                                     |
| Crustacea  | EC50  | Water flea ( <i>Daphnia magna</i> )           | > 1000 mg/l, 48 hours               |
| Fish   | LC50  | Mummichog ( <i>Fundulus heteroclitus</i> )    | > 1000 mg/l, 96 hours               |
| <b>Persistence and degradability</b>                         | No data is available on the degradability of this product.  |   |                                     |
| <b>Bioaccumulative potential</b>                             | No data available.  |   |                                     |
| <b>Partition coefficient n-octanol / water (log Kow)</b>     |   |   |                                     |
| n-Butane   |   |   | 2.89                                |
| Propane  |   |   | 2.36                                |
| <b>Mobility in soil</b>                                      | No data available.  |   |                                     |
| <b>Other adverse effects</b>                                 | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |   |                                     |

### 13. Disposal considerations

---

|  |   |
|--|---|
| <b>Disposal of waste from residues / unused products</b> | This material and its container must be disposed of as hazardous waste. If discarded, this product is considered a RCRA ignitable waste, D001. Consult authorities before disposal. Empty container can be recycled. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations. |
| <b>Hazardous waste code</b>                              | D001: Waste Flammable material with a flash point <140 F  |
| <b>Contaminated packaging</b>                            | Do not re-use empty containers.   |

### 14. Transport information

---

#### DOT

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| <b>UN number</b>                    | UN1950                                |
| <b>UN proper shipping name</b>      | Aerosols, flammable, limited quantity |
| <b>Transport hazard class(es)</b>   |                                       |
| <b>Class</b>                        | 2.1                                   |
| <b>Subsidiary risk</b>              | -                                     |
| <b>Label(s)</b>                     | 2.1                                   |
| <b>Packing group</b>                | Not applicable.                       |
| <b>Special precautions for user</b> | Not available.                        |
| <b>Special provisions</b>           | N82                                   |
| <b>Packaging exceptions</b>         | 306                                   |
| <b>Packaging non bulk</b>           | 304                                   |
| <b>Packaging bulk</b>               | None                                  |

#### IATA

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| <b>UN number</b>                    | UN1950                                |
| <b>UN proper shipping name</b>      | Aerosols, flammable, limited quantity |
| <b>Transport hazard class(es)</b>   |                                       |
| <b>Class</b>                        | 2.1                                   |
| <b>Subsidiary risk</b>              | -                                     |
| <b>Packing group</b>                | Not applicable.                       |
| <b>Environmental hazards</b>        | No.                                   |
| <b>ERG Code</b>                     | 10L                                   |
| <b>Special precautions for user</b> | Not available.                        |
| <b>Other information</b>            |                                       |
| <b>Passenger and cargo aircraft</b> | Allowed.                              |
| <b>Cargo aircraft only</b>          | Allowed.                              |

#### IMDG

|                                     |                            |
|-------------------------------------|----------------------------|
| <b>UN number</b>                    | UN1950                     |
| <b>UN proper shipping name</b>      | AEROSOLS, LIMITED QUANTITY |
| <b>Transport hazard class(es)</b>   |                            |
| <b>Class</b>                        | 2                          |
| <b>Subsidiary risk</b>              | -                          |
| <b>Packing group</b>                | Not applicable.            |
| <b>Environmental hazards</b>        |                            |
| <b>Marine pollutant</b>             | No.                        |
| <b>EmS</b>                          | F-D, S-U                   |
| <b>Special precautions for user</b> | Not available.             |

### 15. Regulatory information

---

|   |  |
|---|--|
| <b>US federal regulations</b>   | This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. |
| <b>TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)</b>            | Not regulated.   |
| <b>SARA 304 Emergency release notification</b>                                  | Not regulated.   |
| <b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>       | Not listed.  |
| <b>US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance</b> | Not listed.  |
| <b>CERCLA Hazardous Substance List (40 CFR 302.4)</b>                           | Not listed.  |

**CERCLA Hazardous Substances: Reportable quantity**

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.**Food and Drug Administration (FDA)** Not regulated.**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 311/312** Immediate Hazard - Yes**Hazard categories** Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No**US state regulations****US. New Jersey RTK - Substances: Listed substance**

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

**US. Massachusetts RTK - Substance List**

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**US. Pennsylvania RTK - Hazardous Substances**

Calcium carbonate (CAS 1317-65-3)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

**US. Rhode Island RTK**

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

Titanium dioxide (CAS 13463-67-7)

Listed: September 2, 2011

**Volatile organic compounds (VOC) regulations****EPA****Aerosol coatings (40 CFR 59, Subpt. E)** Compliant**State****Aerosol coatings** This product is regulated as a Ground Traffic and Marking Coating. This product is compliant for sale in all 50 states.**Maximum incremental reactivity (MIR)** 0.58**International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)         | No                     |
| Canada               | Domestic Substances List (DSL)                             | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                        | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC) | No                     |

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | Yes                    |
| New Zealand                 | New Zealand Inventory  | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

---

|                            |  |
|----------------------------|--|
| <b>Issue date</b>          | 10-01-2013   |
| <b>Prepared by</b>         | Allison Cho  |
| <b>Version #</b>           | 01   |
| <b>Further information</b> | Not available.   |
| <b>HMIS® ratings</b>       | Health: 1*<br>Flammability: 4<br>Physical hazard: 0<br>Personal protection: B  |
| <b>NFPA ratings</b>        | Health: 1<br>Flammability: 4<br>Instability: 0   |
| <b>Disclaimer</b>          | The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries. |





# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Upside Down Marking Paints - Alert Orange

**Other means of identification**

**Product code** 18204

**Recommended use** Coating

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service** 800-272-4620

**24-Hour Emergency (CHEMTREC)** 800-424-9300 (US)

703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
Gases under pressure Liquefied gas

**Health hazards** Carcinogenicity Category 2  
Aspiration hazard Category 1

**Environmental hazards** Hazardous to the aquatic environment, long-term hazard Category 3

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Suspected of causing cancer.

**Precautionary statement**

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If swallowed: Call a physician/poison center immediately. Do NOT induce vomiting. If exposed or concerned: Get medical attention.

**Storage** Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose or store at temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

**Hazard(s) not otherwise classified (HNOC)** Harmful to aquatic life with long lasting effects.

**Supplemental information**

53.89% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

### 3. Composition/information on ingredients

---

#### Mixtures

| Chemical name                               | Common name and synonyms | CAS number | %       |
|---|--------------------------|------------|---------|
| Water                                       |                          | 7732-18-5  | 20 - 30 |
| Calcium carbonate                           |                          | 1317-65-3  | 10 - 20 |
| n-Butane                                    |                          | 106-97-8   | 10 - 20 |
| Propane                                     |                          | 74-98-6    | 10 - 20 |
| Solvent naphtha (petroleum), light aliph.   |                          | 64742-89-8 | 10 - 20 |
| Distillates (petroleum), hydrotreated light |                          | 64742-47-8 | 1 - 5   |
| Titanium dioxide                            |                          | 13463-67-7 | < 1     |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

---

|   |  |
|---|--|
| <b>Inhalation</b>   | Move to fresh air. Call a physician if symptoms develop or persist.  |
| <b>Skin contact</b>   | Wash off with soap and water. Take off contaminated clothing and wash before reuse. Get medical attention if irritation develops and persists.   |
| <b>Eye contact</b>  | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.   |
| <b>Ingestion</b>  | Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis. |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Direct contact with eyes may cause temporary irritation.   |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically.   |
| <b>General information</b>  | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.   |

### 5. Fire-fighting measures

---

|  |  |
|--|--|
| <b>Suitable extinguishing media</b>                                  | Small Fires: Powder. Water spray. Carbon dioxide (CO <sub>2</sub> ). Dry sand.<br><br>Large Fires: Water spray. Alcohol resistant foam.  |
| <b>Unsuitable extinguishing media</b>                                | None known.  |
| <b>Specific hazards arising from the chemical</b>                    | Contents under pressure. Pressurized container may explode when exposed to heat or flame.  |
| <b>Special protective equipment and precautions for firefighters</b> | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.   |
| <b>Fire-fighting equipment/instructions</b>                          | In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| <b>General fire hazards</b>  | Extremely flammable aerosol.   |

### 6. Accidental release measures

---

|  |  |
|--|--|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.   |
| <b>Methods and materials for containment and cleaning up</b>               | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. |
| <b>Environmental precautions</b>   | Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.   |

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

### Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Store in a well-ventilated place. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                        | Type | Value                  | Form                 |
|-----------------------------------|------|------------------------|----------------------|
| Calcium carbonate (CAS 1317-65-3) | PEL  | 5 mg/m <sup>3</sup>    | Respirable fraction. |
| Propane (CAS 74-98-6)             | PEL  | 15 mg/m <sup>3</sup>   | Total dust.          |
|                                   |      | 1800 mg/m <sup>3</sup> |                      |
| Titanium dioxide (CAS 13463-67-7) | PEL  | 1000 ppm               | Total dust.          |
|                                   |      | 15 mg/m <sup>3</sup>   |                      |

#### US. ACGIH Threshold Limit Values

| Components                        | Type | Value                |
|-----------------------------------|------|----------------------|
| n-Butane (CAS 106-97-8)           | STEL | 1000 ppm             |
| Titanium dioxide (CAS 13463-67-7) | TWA  | 10 mg/m <sup>3</sup> |

#### US. NIOSH: Pocket Guide to Chemical Hazards

| Components   | Type | Value                  | Form        |
|--|------|------------------------|-------------|
| Calcium carbonate (CAS 1317-65-3)                            | TWA  | 5 mg/m <sup>3</sup>    | Respirable. |
| Distillates (petroleum), hydrotreated light (CAS 64742-47-8) | TWA  | 10 mg/m <sup>3</sup>   | Total       |
|  |      | 100 mg/m <sup>3</sup>  |             |
| n-Butane (CAS 106-97-8)                                      | TWA  | 1900 mg/m <sup>3</sup> |             |
|  |      | 800 ppm                |             |
| Propane (CAS 74-98-6)  | TWA  | 1800 mg/m <sup>3</sup> |             |
|  |      | 1000 ppm               |             |

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin protection

##### Hand protection

Wear protective gloves such as nitrile or rubber.

##### Other

Wear appropriate chemical resistant clothing.

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Air monitoring is needed to determine actual employee exposure levels.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

Material name: Upside Down Marking Paints - Alert Orange

1055 Version #: 01 Issue date: 10-01-2013

SDS US

3 / 8

|   |                           |
|---|---------------------------|
| <b>Physical state</b>                               | Liquid.                   |
| <b>Form</b>   | Aerosol.                  |
| <b>Color</b>  | Orange.                   |
| <b>Odor</b>   | Aromatic.                 |
| <b>Odor threshold</b>                               | Not available.            |
| <b>pH</b>   | Not available.            |
| <b>Melting point/freezing point</b>                 | -138.8 °F (-94.9 °C)      |
| <b>Initial boiling point and boiling range</b>      | -47.2 °F (-44 °C)         |
| <b>Flash point</b>                                  | -2.2 °F (-19 °C)          |
| <b>Evaporation rate</b>                             | Not available.            |
| <b>Flammability (solid, gas)</b>                    | Not available.            |
| <b>Upper/lower flammability or explosive limits</b> |                           |
| <b>Flammability limit - lower (%)</b>               | 1.5 %                     |
| <b>Flammability limit - upper (%)</b>               | 10.9 %                    |
| <b>Vapor pressure</b>                               | 2221.9 hPa estimated      |
| <b>Vapor density</b>                                | > 1 (air = 1)             |
| <b>Relative density</b>                             | 0.77 - 0.85               |
| <b>Solubility (water)</b>                           | Not available.            |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.            |
| <b>Auto-ignition temperature</b>                    | 410 °F (210 °C) estimated |
| <b>Decomposition temperature</b>                    | Not available.            |
| <b>Viscosity (kinematic)</b>                        | Not available.            |
| <b>Percent volatile</b>                             | 75 %                      |

## 10. Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.   |
| <b>Possibility of hazardous reactions</b> | No dangerous reaction known under conditions of normal use.                                   |
| <b>Conditions to avoid</b>                | Heat, flames and sparks. Contact with incompatible materials.                                 |
| <b>Incompatible materials</b>             | Strong oxidizing agents. Acids. Fluorine. Chlorine. Nitrates.                                 |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.  |

## 11. Toxicological information

### Information on likely routes of exposure

|   |  |
|---|--|
| <b>Ingestion</b>  | May be fatal if swallowed and enters airways.            |
| <b>Inhalation</b>   | Prolonged inhalation may be harmful.                     |
| <b>Skin contact</b>   | Prolonged skin contact may cause temporary irritation.   |
| <b>Eye contact</b>  | Direct contact with eyes may cause temporary irritation. |
| <b>Symptoms related to the physical, chemical and toxicological characteristics</b> | Direct contact with eyes may cause temporary irritation. |

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

| <b>Product</b>                            | <b>Species</b> | <b>Test Results</b>                  |
|---|----------------|--------------------------------------|
| Upside Down Marking Paints - Alert Orange |                |                                      |
| <b>Acute</b>                              |                |                                      |
| <i>Dermal</i>                             |                |                                      |
| LD50                                      | Rabbit         | 25990.8555 mg/kg estimated           |
| <i>Inhalation</i>                         |                |                                      |
| LC50                                      | Rat            | 8179.4048 mg/l, 15 Minutes estimated |

| Product   | Species  | Test Results                        |
|---|--|-------------------------------------|
|   |  | 6351.3516 mg/l, 4 hours estimated   |
| <i>Oral</i><br>LD50   | Rat  | 90459.0625 mg/kg estimated          |
| <b>Chronic</b><br><i>Oral</i><br>LD50                         | Mouse  | 2626.2632 g/kg estimated            |
| <b>Skin corrosion/irritation</b>                              | Prolonged skin contact may cause temporary irritation.   |                                     |
| <b>Serious eye damage/eye irritation</b>                      | Direct contact with eyes may cause temporary irritation.   |                                     |
| <b>Respiratory sensitization</b>                              | Not available.   |                                     |
| <b>Skin sensitization</b>                                     | This product is not expected to cause skin sensitization.  |                                     |
| <b>Germ cell mutagenicity</b>                                 | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |                                     |
| <b>Carcinogenicity</b>  | Suspected of causing cancer.   |                                     |
| <b>IARC Monographs. Overall Evaluation of Carcinogenicity</b> |  |                                     |
| Titanium dioxide (CAS 13463-67-7)                             |  | 2B Possibly carcinogenic to humans. |
| <b>Reproductive toxicity</b>                                  | This product is not expected to cause reproductive or developmental effects.                                     |                                     |
| <b>Specific target organ toxicity - single exposure</b>       | Not classified.  |                                     |
| <b>Specific target organ toxicity - repeated exposure</b>     | Not classified.  |                                     |
| <b>Aspiration hazard</b>                                      | May be fatal if swallowed and enters airways.  |                                     |
| <b>Chronic effects</b>  | Prolonged inhalation may be harmful.   |                                     |

## 12. Ecological information

|  |   |   |                                     |
|--|---|---|-------------------------------------|
| <b>Ecotoxicity</b>   | Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.   |   |                                     |
| <b>Product</b>   | <b>Species</b>  |   |                                     |
| <b>Test Results</b>  |   |   |                                     |
| Upside Down Marking Paints - Alert Orange                    |   |   |                                     |
| <i>Acute</i>   |   |   |                                     |
| Crustacea  | EC50  | Daphnia                                       | 9545.4541 mg/l, 48 hours estimated  |
| Fish   | LC50  | Fish  | 15568.5059 mg/l, 96 hours estimated |
| <b>Components</b>  | <b>Species</b>  |   |                                     |
| <b>Test Results</b>  |   |   |                                     |
| Distillates (petroleum), hydrotreated light (CAS 64742-47-8) |   |   |                                     |
| <i>Acute</i>   |   |   |                                     |
|  | EC50  | Invertebrate (saltwater)                      | 4720 mg/l, 96 hours                 |
| <b>Aquatic</b>   |   |   |                                     |
| <i>Acute</i>   |   |   |                                     |
| Fish   | LC50  | Bluegill ( <i>Lepomis macrochirus</i> )       | 1740 mg/l, 96 hours                 |
|  |   | Fathead minnow ( <i>Pimephales promelas</i> ) | 45 mg/l, 96 hours                   |
| Titanium dioxide (CAS 13463-67-7)                            |   |   |                                     |
| <b>Aquatic</b>   |   |   |                                     |
| Crustacea  | EC50  | Water flea ( <i>Daphnia magna</i> )           | > 1000 mg/l, 48 hours               |
| Fish   | LC50  | Mummichog ( <i>Fundulus heteroclitus</i> )    | > 1000 mg/l, 96 hours               |
| <b>Persistence and degradability</b>                         | No data is available on the degradability of this product.  |   |                                     |
| <b>Bioaccumulative potential</b>                             | No data available.  |   |                                     |
| <b>Partition coefficient n-octanol / water (log Kow)</b>     |   |   |                                     |
| n-Butane   |   |   | 2.89                                |
| Propane  |   |   | 2.36                                |
| <b>Mobility in soil</b>                                      | No data available.  |   |                                     |
| <b>Other adverse effects</b>                                 | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |   |                                     |

### 13. Disposal considerations

---

|  |   |
|--|---|
| <b>Disposal of waste from residues / unused products</b> | This material and its container must be disposed of as hazardous waste. If discarded, this product is considered a RCRA ignitable waste, D001. Consult authorities before disposal. Empty container can be recycled. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations. |
| <b>Hazardous waste code</b>                              | D001: Waste Flammable material with a flash point <140 F  |
| <b>Contaminated packaging</b>                            | Do not re-use empty containers.   |

### 14. Transport information

---

#### DOT

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| <b>UN number</b>                    | UN1950                                |
| <b>UN proper shipping name</b>      | Aerosols, flammable, limited quantity |
| <b>Transport hazard class(es)</b>   |                                       |
| <b>Class</b>                        | 2.1                                   |
| <b>Subsidiary risk</b>              | -                                     |
| <b>Label(s)</b>                     | 2.1                                   |
| <b>Packing group</b>                | Not applicable.                       |
| <b>Special precautions for user</b> | Not available.                        |
| <b>Special provisions</b>           | N82                                   |
| <b>Packaging exceptions</b>         | 306                                   |
| <b>Packaging non bulk</b>           | 304                                   |
| <b>Packaging bulk</b>               | None                                  |

#### IATA

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| <b>UN number</b>                    | UN1950                                |
| <b>UN proper shipping name</b>      | Aerosols, flammable, limited quantity |
| <b>Transport hazard class(es)</b>   |                                       |
| <b>Class</b>                        | 2.1                                   |
| <b>Subsidiary risk</b>              | -                                     |
| <b>Packing group</b>                | Not applicable.                       |
| <b>Environmental hazards</b>        | No.                                   |
| <b>ERG Code</b>                     | 10L                                   |
| <b>Special precautions for user</b> | Not available.                        |
| <b>Other information</b>            |                                       |
| <b>Passenger and cargo aircraft</b> | Allowed.                              |
| <b>Cargo aircraft only</b>          | Allowed.                              |

#### IMDG

|                                     |                            |
|-------------------------------------|----------------------------|
| <b>UN number</b>                    | UN1950                     |
| <b>UN proper shipping name</b>      | AEROSOLS, LIMITED QUANTITY |
| <b>Transport hazard class(es)</b>   |                            |
| <b>Class</b>                        | 2                          |
| <b>Subsidiary risk</b>              | -                          |
| <b>Packing group</b>                | Not applicable.            |
| <b>Environmental hazards</b>        |                            |
| <b>Marine pollutant</b>             | No.                        |
| <b>EmS</b>                          | F-D, S-U                   |
| <b>Special precautions for user</b> | Not available.             |

### 15. Regulatory information

---

|   |  |
|---|--|
| <b>US federal regulations</b>   | This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. |
| <b>TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)</b>            | Not regulated.   |
| <b>SARA 304 Emergency release notification</b>                                  | Not regulated.   |
| <b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>       | Not listed.  |
| <b>US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance</b> | Not listed.  |
| <b>CERCLA Hazardous Substance List (40 CFR 302.4)</b>                           | Not listed.  |

**CERCLA Hazardous Substances: Reportable quantity**

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.**Food and Drug Administration (FDA)** Not regulated.**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 311/312** Immediate Hazard - Yes**Hazard categories** Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No**US state regulations****US. New Jersey RTK - Substances: Listed substance**

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

**US. Massachusetts RTK - Substance List**

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**US. Pennsylvania RTK - Hazardous Substances**

Calcium carbonate (CAS 1317-65-3)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

**US. Rhode Island RTK**

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

Titanium dioxide (CAS 13463-67-7)

Listed: September 2, 2011

**Volatile organic compounds (VOC) regulations****EPA****Aerosol coatings (40 CFR 59, Subpt. E)** Compliant**State****Aerosol coatings** This product is regulated as a Ground Traffic and Marking Coating. This product is compliant for sale in all 50 states.**Maximum incremental reactivity (MIR)** 0.58**International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)         | No                     |
| Canada               | Domestic Substances List (DSL)                             | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                        | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC) | No                     |

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | Yes                    |
| New Zealand                 | New Zealand Inventory  | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

---

|                            |  |
|----------------------------|--|
| <b>Issue date</b>          | 10-01-2013   |
| <b>Prepared by</b>         | Allison Cho  |
| <b>Version #</b>           | 01   |
| <b>Further information</b> | Not available.   |
| <b>HMIS® ratings</b>       | Health: 1*<br>Flammability: 4<br>Physical hazard: 0<br>Personal protection: B  |
| <b>NFPA ratings</b>        | Health: 1<br>Flammability: 4<br>Instability: 0   |
| <b>Disclaimer</b>          | The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries. |