

BI-METAL RECIPROCATING SAW BLADES

Long Lasting, Fast Cutting and Versatile

LONG LIFE

Patented tooth design provides long blade life

















EFFICIENT CUTTING

Optimized for specific applications

DURABLE CONSTRUCTION

Shatter resistant, bi-metal design provides the flexibility and durability single-metal blades can't



| TPI | LENGTH x WIDTH x THICKNESS | | 1-PACK | 5-PACK | 25-PACK | 50-PACK | APPLICATION |  | |
|-------|----------------------------|--------|----------------|-------------|------------|-------------|--------------|---|---|
| | IN | MM | PROD NO | PROD NO | PROD NO | PROD NO | | | |
| 4 | 6 x 3/4 | x .050 | 152 x 19 x 1.3 | 20574S634R | 20575634R | — | — |  | |
| 6 | 4 x 3/4 | x .050 | 102 x 19 x 1.3 | — | 20449456RP | — | — |  | |
| 6 | 6 x 3/4 | x .050 | 152 x 19 x 1.3 | 20571S636RP | 20570636RP | 20497B636RP | — |  | |
| 6 | 6 x 3/4 | x .035 | 152 x 19 x .9 | 20559S606R | 20560606R | 20492B606R | — |  | |
| 6 | 6 x 7/16 | x .050 | 152 x 11 x 1.3 | 20557S676RC | 20556676RC | — | — |  | |
| 6 | 6 x 3/4 | x .050 | 152 x 19 x 1.3 | 20573S656R | 20572656R | 20530B656R | 227500SB656R |  | |
| 6 | 9 x 3/4 | x .050 | 229 x 19 x 1.3 | 20587S956R | 20582956R | 20558B956R | 227520SB956R |  | |
| 6 | 12 x 3/4 | x .050 | 305 x 19 x 1.3 | 20586S156R | 20585156R | 20495B156R | 227550SB156R |  | |
| 10 | 6 x 3/4 | x .035 | 152 x 19 x .9 | 20561S610R | 20562610R | 20493B610R | 227610SB610R |  | |
| 10 | 8 x 3/4 | x .050 | 203 x 19 x 1.3 | 20581S810R | 20580810R | 20590B810R | 227530SB810R |  | |
| 10/14 | 6 x 3/4 | x .050 | 152 x 19 x 1.3 | 20592650R* | 20374650R5 | 20515B650R | — |  | • |
| 10/14 | 8 x 3/4 | x .050 | 203 x 19 x 1.3 | — | 20577850R | 20535B850R | — |  | • |
| 10/14 | 12 x 3/4 | x .050 | 305 x 19 x 1.3 | 20584S110R | 20583110R | 20491B110R | 227580SB110R |  | • |
| 10/14 | 6 x 3/4 | x .035 | 152 x 19 x .9 | — | 12129635R | — | — |  | • |
| 10/14 | 8 x 3/4 | x .035 | 203 x 19 x .9 | — | 12130835R | — | — |  | • |

* This item is a 2-pack



Two 10/14 TPI General Purpose reciprocating blades featuring T2 Technology. The 0.035" thick blades are ideal for cutting wood, metal and plastic 12129635R, 12130835R



LENOX T2™ TECHNOLOGY RECIPROCATING SAW BLADES

A revolutionary new blade design that delivers up to 100% longer blade life and 25% faster performance in metal cutting applications versus the prior generation of LENOX reciprocating saw blades.

BI-METAL RECIPROCATING SAW BLADES

Long Lasting, Fast Cutting and Versatile

LONG LIFE

Patented tooth design provides long blade life

















EFFICIENT CUTTING

Optimized for specific applications

DURABLE CONSTRUCTION

Shatter resistant, bi-metal design provides the flexibility and durability single-metal blades can't



| TPI | LENGTH x WIDTH x THICKNESS | | 1-PACK | 5-PACK | 25-PACK | 50-PACK | APPLICATION |  | |
|-------|----------------------------|--------|----------------|-------------|------------|-------------|--------------|---|---|
| | IN | MM | PROD NO | PROD NO | PROD NO | PROD NO | | | |
| 4 | 6 x 3/4 | x .050 | 152 x 19 x 1.3 | 20574S634R | 20575634R | — | — |  | |
| 6 | 4 x 3/4 | x .050 | 102 x 19 x 1.3 | — | 20449456RP | — | — |  | |
| 6 | 6 x 3/4 | x .050 | 152 x 19 x 1.3 | 20571S636RP | 20570636RP | 20497B636RP | — |  | |
| 6 | 6 x 3/4 | x .035 | 152 x 19 x .9 | 20559S606R | 20560606R | 20492B606R | — |  | |
| 6 | 6 x 7/16 | x .050 | 152 x 11 x 1.3 | 20557S676RC | 20556676RC | — | — |  | |
| 6 | 6 x 3/4 | x .050 | 152 x 19 x 1.3 | 20573S656R | 20572656R | 20530B656R | 227500SB656R |  | |
| 6 | 9 x 3/4 | x .050 | 229 x 19 x 1.3 | 20587S956R | 20582956R | 20558B956R | 227520SB956R |  | |
| 6 | 12 x 3/4 | x .050 | 305 x 19 x 1.3 | 20586S156R | 20585156R | 20495B156R | 227550SB156R |  | |
| 10 | 6 x 3/4 | x .035 | 152 x 19 x .9 | 20561S610R | 20562610R | 20493B610R | 227610SB610R |  | |
| 10 | 8 x 3/4 | x .050 | 203 x 19 x 1.3 | 20581S810R | 20580810R | 20590B810R | 227530SB810R |  | |
| 10/14 | 6 x 3/4 | x .050 | 152 x 19 x 1.3 | 20592650R* | 20374650R5 | 20515B650R | — |  | • |
| 10/14 | 8 x 3/4 | x .050 | 203 x 19 x 1.3 | — | 20577850R | 20535B850R | — |  | • |
| 10/14 | 12 x 3/4 | x .050 | 305 x 19 x 1.3 | 20584S110R | 20583110R | 20491B110R | 227580SB110R |  | • |
| 10/14 | 6 x 3/4 | x .035 | 152 x 19 x .9 | — | 12129635R | — | — |  | • |
| 10/14 | 8 x 3/4 | x .035 | 203 x 19 x .9 | — | 12130835R | — | — |  | • |

* This item is a 2-pack



Two 10/14 TPI General Purpose reciprocating blades featuring T2 Technology. The 0.035" thick blades are ideal for cutting wood, metal and plastic 12129635R, 12130835R



LENOX T2™ TECHNOLOGY RECIPROCATING SAW BLADES

A revolutionary new blade design that delivers up to 100% longer blade life and 25% faster performance in metal cutting applications versus the prior generation of LENOX reciprocating saw blades.