


## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





## 22747EE00 2 1/2" LD EN/E Conduit Dody

Catalog Number	227475599
Manufacturer	Crouse Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 5 Conduit Outlet Body Malleable Iron, LB Shape, Built-In Rollers, 2-1/2"
Weight per unit	11.5 (lbs/each)
Product Category	Bodies & Covers
Features	
dimensions	13.6000 IN X 4.3100 IN X 5.4000 IN
Form	Form 5
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Height	4.31
Hub Size	
Length	40.70
Width	5.40
Descriptions	
Description	2-1/2" LB FM5 CONDUIT BODY
extra long description	
Features	Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bendin conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h
Long Description	Eaton Crouse-Hinds series Condulet Form 5 conduit outlet body, Malleable iron, LB shape, Built-in rollers, 2-1/2"
Product Type	2-1/2 Form 5 LB Cond Body Malleable

## **Manufacturer Information**

Brand	Eaton
GTIN	00782274755991
Manufacturers Part Number	LB250M
UPC	782274755991



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	gories
Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Availability	
Status	Inactive
Packaging	
Carton	1
Weight Per each	11.45
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other

UL 514B, CSA C22.2, CUL