

Seoprene 105°C - Black Portable Cord

UL Listed – Flexible and tough jacket. Offers a wide useable temperature range of -50°C to 105°C. Seoprene provides excellent abrasion, ozone, sunlight, chemical, oil, water, and mold resistance along with non-wicking lightweight polypropylene fillers. Water resistant with high dielectric insulation. Lightweight, long lasting, easy to carry and handle. All components are recyclable and non-hazardous for environmental landfill disposal. Federal and Military use under Federal Spec. JC-580B. UL Listed SE00W 600V and SJEOOW 300V to NEC Article 400, CSA approved ST00W or SJTOOW (TPE) -50°C to 105°C. MSHA approved for flame resistance in mining applications.



| PART NO | SIZE | TYPE | JACKET COLOR | PKG WT | LENGTH IN FT |
|--------------|------|--------|--------------|--------|--------------|
| 23285-04-08 | 18/2 | SJEW | Black | 11 | 250 |
| 23385-04-08 | 18/3 | SJEW | Black | 14 | 250 |
| 23286-04-08 | 16/2 | SJEW | Black | 14 | 250 |
| 23386-04-08 | 16/3 | SJEW | Black | 17 | 250 |
| 23486-04-08 | 16/4 | SJEW | Black | 20 | 250 |
| 23287-04-08 | 14/2 | SJEW | Black | 17 | 250 |
| 23387-04-08 | 14/3 | SJEW | Black | 21 | 250 |
| 23487-04-08 | 14/4 | SJEW | Black | 26 | 250 |
| 23288-04-08 | 12/2 | SJEW | Black | 24 | 250 |
| 23388-04-08 | 12/3 | SJEW | Black | 31 | 250 |
| 23488-04-08 | 12/4 | SJEW | Black | 39 | 250 |
| 23389-66-08 | 10/3 | SJEW | Black | 22 | 100 |
| 23225-04-08 | 18/2 | SJEOOW | Black | 11 | 250 |
| 23325-04-08 | 18/3 | SJEOOW | Black | 14 | 250 |
| 23425-04-08 | 18/4 | SJEOOW | Black | 17 | 250 |
| 23226-04-08 | 16/2 | SJEOOW | Black | 14 | 250 |
| 23326-04-08 | 16/3 | SJEOOW | Black | 17 | 250 |
| 23426-04-08 | 16/4 | SJEOOW | Black | 20 | 250 |
| 23227-04-08 | 14/2 | SJEOOW | Black | 17 | 250 |
| 23327-04-08 | 14/3 | SJEOOW | Black | 21 | 250 |
| 23427-04-08 | 14/4 | SJEOOW | Black | 26 | 250 |
| 23228-04-08 | 12/2 | SJEOOW | Black | 25 | 250 |
| 23328-04-08 | 12/3 | SJEOOW | Black | 31 | 250 |
| 23428-04-08 | 12/4 | SJEOOW | Black | 40 | 250 |
| 23229-04-08 | 10/2 | SJEOOW | Black | 42 | 250 |
| 23329-04-08 | 10/3 | SJEOOW | Black | 54 | 250 |
| 23429-05-08 | 10/4 | SJEOOW | Black | 69 | 500 |
| 22225-04-08 | 18/2 | SE00W | Black | 15 | 250 |
| 22325-04-08 | 18/3 | SE00W | Black | 18 | 250 |
| 22226-04-08 | 16/2 | SE00W | Black | 18 | 250 |
| 22326-04-08 | 16/3 | SE00W | Black | 21 | 250 |
| 22227-05-08 | 14/2 | SE00W | Black | 63 | 500 |
| 22327-05-08 | 14/3 | SE00W | Black | 75 | 500 |
| 22427-05-08 | 14/4 | SE00W | Black | 92 | 500 |
| 22228-05-08 | 12/2 | SE00W | Black | 82 | 500 |
| 22328-05-08 | 12/3 | SE00W | Black | 100 | 500 |
| 22428-05-08 | 12/4 | SE00W | Black | 121 | 500 |
| 22229-05-08 | 10/2 | SE00W | Black | 104 | 500 |
| 22329-05-08 | 10/3 | SE00W | Black | 130 | 500 |
| 22429-05-08 | 10/4 | SE00W | Black | 158 | 500 |
| 22320-04-08* | 8/3 | SE00W | Black | 83 | 250 |
| 22420-04-08* | 8/4 | SE00W | Black | 107 | 250 |
| 22321-04-08* | 6/3 | SE00W | Black | 119 | 250 |
| 22421-04-08* | 6/4 | SE00W | Black | 149 | 250 |

* Not UL Listed or CSA approved

Bulk Vinyl Portable Cords

UL Listed – A firm compact cylindrical cord cabled for maximum flexibility and roundness per UL 62. Easy to remove jacket. Rated -20°C to 60°C. PVC cords provide excellent abrasion, ozone and chemical resistance. UL Listed and CSA approved 300V SJTW cable for use in cord sets.

| PART NO | SIZE | TYPE | JACKET COLOR | PKG WT | LENGTH IN FT |
|-------------|------|------|--------------|--------|--------------|
| 20205-66-03 | 18/2 | SJTW | Orange | 11 | 250 |
| 20305-66-03 | 18/3 | SJTW | Orange | 13 | 250 |
| 20206-66-03 | 16/2 | SJTW | Orange | 13 | 250 |
| 20306-66-03 | 16/3 | SJTW | Orange | 16 | 250 |
| 20307-66-03 | 14/3 | SJTW | Orange | 21 | 250 |
| 20308-66-03 | 12/3 | SJTW | Orange | 31 | 250 |
| 20309-04-03 | 10/3 | SJTW | Orange | 56 | 250 |

Seoprene 105°C - Black Portable Cord

UL Listed – Flexible and tough jacket. Offers a wide useable temperature range of -50°C to 105°C. Seoprene provides excellent abrasion, ozone, sunlight, chemical, oil, water, and mold resistance along with non-wicking lightweight polypropylene fillers. Water resistant with high dielectric insulation. Lightweight, long lasting, easy to carry and handle. All components are recyclable and non-hazardous for environmental landfill disposal. Federal and Military use under Federal Spec. JC-580B. UL Listed SE00W 600V and SJEOOW 300V to NEC Article 400, CSA approved ST00W or SJTOOW (TPE) -50°C to 105°C. MSHA approved for flame resistance in mining applications.



| PART NO | SIZE | TYPE | JACKET COLOR | PKG WT | LENGTH IN FT |
|--------------|------|--------|--------------|--------|--------------|
| 23285-04-08 | 18/2 | SJEW | Black | 11 | 250 |
| 23385-04-08 | 18/3 | SJEW | Black | 14 | 250 |
| 23286-04-08 | 16/2 | SJEW | Black | 14 | 250 |
| 23386-04-08 | 16/3 | SJEW | Black | 17 | 250 |
| 23486-04-08 | 16/4 | SJEW | Black | 20 | 250 |
| 23287-04-08 | 14/2 | SJEW | Black | 17 | 250 |
| 23387-04-08 | 14/3 | SJEW | Black | 21 | 250 |
| 23487-04-08 | 14/4 | SJEW | Black | 26 | 250 |
| 23288-04-08 | 12/2 | SJEW | Black | 24 | 250 |
| 23388-04-08 | 12/3 | SJEW | Black | 31 | 250 |
| 23488-04-08 | 12/4 | SJEW | Black | 39 | 250 |
| 23389-66-08 | 10/3 | SJEW | Black | 22 | 100 |
| 23225-04-08 | 18/2 | SJEOOW | Black | 11 | 250 |
| 23325-04-08 | 18/3 | SJEOOW | Black | 14 | 250 |
| 23425-04-08 | 18/4 | SJEOOW | Black | 17 | 250 |
| 23226-04-08 | 16/2 | SJEOOW | Black | 14 | 250 |
| 23326-04-08 | 16/3 | SJEOOW | Black | 17 | 250 |
| 23426-04-08 | 16/4 | SJEOOW | Black | 20 | 250 |
| 23227-04-08 | 14/2 | SJEOOW | Black | 17 | 250 |
| 23327-04-08 | 14/3 | SJEOOW | Black | 21 | 250 |
| 23427-04-08 | 14/4 | SJEOOW | Black | 26 | 250 |
| 23228-04-08 | 12/2 | SJEOOW | Black | 25 | 250 |
| 23328-04-08 | 12/3 | SJEOOW | Black | 31 | 250 |
| 23428-04-08 | 12/4 | SJEOOW | Black | 40 | 250 |
| 23229-04-08 | 10/2 | SJEOOW | Black | 42 | 250 |
| 23329-04-08 | 10/3 | SJEOOW | Black | 54 | 250 |
| 23429-05-08 | 10/4 | SJEOOW | Black | 69 | 500 |
| 22225-04-08 | 18/2 | SE00W | Black | 15 | 250 |
| 22325-04-08 | 18/3 | SE00W | Black | 18 | 250 |
| 22226-04-08 | 16/2 | SE00W | Black | 18 | 250 |
| 22326-04-08 | 16/3 | SE00W | Black | 21 | 250 |
| 22227-05-08 | 14/2 | SE00W | Black | 63 | 500 |
| 22327-05-08 | 14/3 | SE00W | Black | 75 | 500 |
| 22427-05-08 | 14/4 | SE00W | Black | 92 | 500 |
| 22228-05-08 | 12/2 | SE00W | Black | 82 | 500 |
| 22328-05-08 | 12/3 | SE00W | Black | 100 | 500 |
| 22428-05-08 | 12/4 | SE00W | Black | 121 | 500 |
| 22229-05-08 | 10/2 | SE00W | Black | 104 | 500 |
| 22329-05-08 | 10/3 | SE00W | Black | 130 | 500 |
| 22429-05-08 | 10/4 | SE00W | Black | 158 | 500 |
| 22320-04-08* | 8/3 | SE00W | Black | 83 | 250 |
| 22420-04-08* | 8/4 | SE00W | Black | 107 | 250 |
| 22321-04-08* | 6/3 | SE00W | Black | 119 | 250 |
| 22421-04-08* | 6/4 | SE00W | Black | 149 | 250 |

* Not UL Listed or CSA approved

Bulk Vinyl Portable Cords

UL Listed – A firm compact cylindrical cord cabled for maximum flexibility and roundness per UL 62. Easy to remove jacket. Rated -20°C to 60°C. PVC cords provide excellent abrasion, ozone and chemical resistance. UL Listed and CSA approved 300V SJTW cable for use in cord sets.

| PART NO | SIZE | TYPE | JACKET COLOR | PKG WT | LENGTH IN FT |
|-------------|------|------|--------------|--------|--------------|
| 20205-66-03 | 18/2 | SJTW | Orange | 11 | 250 |
| 20305-66-03 | 18/3 | SJTW | Orange | 13 | 250 |
| 20206-66-03 | 16/2 | SJTW | Orange | 13 | 250 |
| 20306-66-03 | 16/3 | SJTW | Orange | 16 | 250 |
| 20307-66-03 | 14/3 | SJTW | Orange | 21 | 250 |
| 20308-66-03 | 12/3 | SJTW | Orange | 31 | 250 |
| 20309-04-03 | 10/3 | SJTW | Orange | 56 | 250 |