



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



254DCI2 1-1/2" Diecast Emt Insulated Concrete Tight Conn *Bridgeport Fittings*

| | |
|------------------|---|
| Catalog Number | 254DCI2 |
| Manufacturer | Bridgeport Fittings |
| Description | Connector, Compression, Zinc Die Cast, 105 Degree C Insulated Throat, Size 1 1/2 Inch |
| Weight per unit | 0.5400 (lbs/each) |
| Product Category | Die Cast Insulated Straight CO |

Features

| | |
|----------------|------------------|
| Connector Type | Compression |
| insulation | Insulated Throat |
| media | Yes |

Material, Color, and Finish

| | |
|--------|--------------|
| Finish | Ball burnish |
|--------|--------------|

Dimensions and Weight

| | |
|------|-------|
| Size | 1 1/2 |
|------|-------|

Descriptions

| | |
|------------------------|---|
| Description | 1-1/2" DIECAST EMT INSULATED CONCRETE TIGHT CONN |
| extra long description | BPT 254-DCI2 1-1/2" COMP. CONN. INS |
| Features | Think Orange: Zinc Advantage –Error-free Performance – meets same stringent UL tests as steel. Bridgeport zinc EMT fittings set the standard for EMT. |
| Long Description | Connector, Compression, Zinc Die Cast, 105 Degree C Insulated Throat, Size 1 1/2 Inch |
| Product Type | 1-1/2" Comp. Conn. Ins. Zinc |
| Special Features | Concrete-Tight |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Bridgeport |
| GTIN | 00781747162540 |
| Manufacturers Part Number | 254-DCI2 |
| UPC | 781747162540 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|----------------------|
| Category Description | DIECAST EMT FITTINGS |
| Type | CONNECTOR |

Trade Size

| | |
|------------|-------|
| Trade Size | 1-1/2 |
|------------|-------|



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

| | |
|-----------------|------|
| Carton | 10 |
| Package | 40 |
| Weight Per each | 0.54 |

Uses, Certifications, and Standards

| | |
|-------------|--|
| Application | Used to join steel EMT to box or enclosure. Concrete-tight. 1/2" thru 2" suitable for use with Steel or Aluminum EMT. Insulator rated 105degree C. |
| standard | UL, CSA |