

## **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## 28W76 Turnlok Plug IP67 30A 3PH 480V L1630P Pass & Seymour/Legrand

| Catalog Number                   | 28W76   |
|----------------------------------|---|
| Manufacturer                     | Pass & Seymour/Legrand  |
| Description                      | Locking Watertight Plug, 30AMP 3 480 Volt, Nema Configuration<br>L16-30, Multipoint Sealing System Provides Environmental<br>Protection Of: Nema 4, 4X, 6, 6P and IP67 Rated. |
| Weight per unit                  | 0.8300 (lbs/each)   |
| Product Category                 | Plugs, Connectors, Inlets, Out  |
| atures                           |   |
| amperage rating                  | 30  |
| Cord Type                        | 12/4 S to 8/4 S, 6/4 MSHA, .640" min to .930" max   |
| Material                         | Rubber  |
| Number of Wires                  | 4   |
| Phase                            | 3   |
| Poles                            |   |
| Voltage Rating                   | 480   |
| Wire Size                        | 12-6  |
| escriptions                      |   |
| Description                      | TURNLOK PLUG IP67 30A 3PH 480V L1630P   |
| extra long description           | P&S 28W76 TL PLUG IP67 30A 3PH 480V   |
| Long Description                 | Locking Watertight Plug, 30amp 3 480 volt, NEMA Configuration   |
|                                  | L16-30, multipoint sealing system provides environmental  |
|                                  | protection of: NEMA 4, 4X, 6, 6P and IP67 rated.  |
| Product Type                     | TL Plug IP67 30A 3PH 480V L1630P  |
| Special Features                 | Rated watertight for 1,500 psi high-pressure hosedown, P&S  |
|                                  | Turnlok <sup>®</sup> watertight plugs & connectors feature rugged   |
|                                  | construction, multiple seals to ensure protection against the   |
|                                  | environment and ease of installation.   |
| anufacturer Information          |   |
| Brand                            | LEGRAND-PASS & SEYMOUR  |
| GTIN                             | 00785007033519  |
| Manufacturers Part Number        | 28W76   |
| UPC                              | 785007033519  |
| xonomies, Classifications, and ( | Categories  |
| Category Description             | Residential receptacles   |
| Туре                             | LOCKING PLUG  |
| ade Size                         |   |
| Amperage                         | 30.0  |



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging                           |   |
|-------------------------------------|---|
| Carton                              | 1   |
| Package                             | 10  |
| Weight Per each                     | 0.83  |
| Uses, Certifications, and Standards |   |
| Application                         | High-pressure washdowns. Particle build-up. Condensation.<br>Corrosive substances. Food and beverage processing plants can<br>be harsh, challenging environments. Fortunately, we have a full<br>menu of electrical devices that keep things running smoothly |

|                          | while protecting people and equipment. IEC PIN & SLEEVE<br>DEVICES Watertight Plugs & Connectors ¦ Thermoplastic<br>elastomer body resists water, oils, lubricants and soaps while<br>maintaining NEMA 4, 4X, 6, 6P, and IP65, 66, 67 ratings ¦ Ideal<br>for washdown areas — rated wa |
|--------------------------|--|
| environmental conditions | Moisture Resistance NEMA 4, 4X, 12, 6, 6P/IP65, 66, 67 (Plug &<br>Connector only) Flammability UL94V0 (boxes & wiring device<br>interiors) Operating Temperature -40°C (without impact) to<br>+60°C continuous UV resistance All exposed material s are UV<br>stabilized               |
| nema rating              | L16-30P  |
| standard                 | UL Listed, CSA Listed  |