

÷

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| 290G 3/4" | Alu MK9 | CVR/Gasket |
|--------------|---------|-------------------|
| Crouse-Hinds | | |

| Catalog Number | 290G | |
|------------------------------------|---|--|
| Manufacturer | Crouse-Hinds | |
| Description | Eaton Crouse-Hinds Series Condulet Mark 9 Cover With Integral Gasket, Sheet Aluminum, 3/4" | |
| Weight per unit | 0.0880 (lbs/each) | |
| Product Category | Alum | |
| Features | | |
| Material | Aluminum | |
| Dimensions and Weight | | |
| Height | 4.25 | |
| Length | 4.25 | |
| Width | 0.8 | |
| Descriptions | | |
| Description | 3/4" ALU MK9 CVR/GASKET | |
| extra long description | CRS-H 290G 3/4 SHT AL MARK 9 CVR/GA | |
| Features | Mark 9 copper-free aluminum conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide for access to conductors for maintenance and future system changes. Mark 9 bodies are offered in seven different shapes, and they provide more room for heavier conductors. | |
| Long Description | Eaton Crouse-Hinds series Condulet Mark 9 cover with integral gasket, Sheet aluminum, 3/4" | |
| Product Type | 3/4 SHT AI Mark 9 CVR/Gask | |
| Special Features | With Neoprene Integral Gasket | |
| Manufacturer Information | | |
| Brand | Eaton | |
| GTIN | 00662276016026 | |
| Manufacturers Part Number | 290G | |
| UPC | 662276016026 | |
| Taxonomies, Classifications, and (| Categories | |
| Category Description | | |
| Туре | Cover with integral gasket | |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

| Carton | 1 |
|-----------------|-------|
| Package | 25 |
| Weight Per each | 0.088 |

Uses, Certifications, and Standards

| Application | Ind Facilities & Factories - Industrial Facilities/Factories - Other |
|-------------|--|
| standard | UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D |