

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

30026 Noalox (4	Oz. Bottle)
Catalog Number	30026
Manufacturer	Ideal
Description	Anti-Oxidant Compound, 4 Oz Squeeze Bottle, Petroleum Base, 1.04 Specific Gravity, 310 °F Flash Point, 0.33 LB
Weight per unit	0.3250 (lbs/each)
Product Category	Paint, Chemicals, Etc.
e atures specific gravity	1.04
imensions and Weight	
Size	4 OZ Squeeze Bottle
escriptions	
Description	NOALOX (4 OZ. BOTTLE)
extra long description	IDEAL 30-026 NOALOX (4 OZ CONTAINER
Features	IDEAL Noalox Anti-Oxidant compound improves efficiency and
	service life of aluminum electrical applications. Suspended zinc particles penetrate and cut aluminum oxide, while carrier material excludes air to minimize further oxidation. Provides additional inner-strand and inner-conductor current paths for improved conductivity and cooler connections. For use with pressure-type wire connectors including lugs, taps, service entrances and split-bolts. It is used with all types of pressure-typ wire connectors.
Special Features	Anti-oxidant and anti-seizing compound improves efficiency and service life of aluminum-to-aluminum and aluminum-to-copper electrical connections; Suspended zinc particles penetrate and cut aluminum oxide; Provides additional interstrand and inter-conductor current paths for improved conductivity and cooler connections; Carrier material excludes air to prevent further oxidation; Reduces galling and seizing and promotes good ground continuity on aluminum conduit joints; Improves service life of aluminum ele
Ianufacturer Information	
Brand	Ideal
GTIN	00783250300266
UPC	783250300266
axonomies, Classifications, and	Categories
	WIRE LUBE, MARKERS, & TIES
Туре	Anti-Oxidant Compound



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton		
Package	10	
Weight Per each		
..		

Uses, Certifications, and Standards

standard	
----------	--