

# ETP™ 4000S Series Steel EMT Set Screw Connectors

NEC/CEC:  
Listed for Ordinary Locations

## Application

- To ground and secure EMT raceways to boxes and enclosures.

## Features

- Heavy steel walls.
- Concretetight when taped.
- Pre-set/pre-staked set screws.
- Male hub threads — NPS.
- Available with insulated throat.
- Three-way combination screws 1/2" thru 2".
- Slotted hexhead screw 2-1/2" thru 4".
- Insulated throat connector rated +90 °C (+194 °F).
- 2-1/2" thru 4" rated for threadless Aluminum RMC and steel IMC.

## Materials/Finish

- Steel/zinc plated

## NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E-14895
- CSA Certified: 028507
- NEMA: FB-1



4050S-4100S



4125S - 4400S

Dimensions in Millimeters (Inches)

| Trade Size (Inches) | Body Length | Maximum Diameter | Thread Length | Weight per 100 kg (lb) | Catalog Number | Insulated Throat Catalog Number |
|---------------------|-------------|------------------|---------------|------------------------|----------------|---------------------------------|
| 1/2                 | 26.2 (1.03) | 21.3 (0.84)      | 11.2 (0.44)   | 4.54 (10.00)           | 4050S          | 4050ST                          |
| 3/4                 | 27.7 (1.09) | 27.4 (1.08)      | 11.2 (0.44)   | 6.80 (15.00)           | 4075S          | 4075ST                          |
| 1                   | 30.2 (1.19) | 33.3 (1.31)      | 11.2 (0.44)   | 10.43 (23.00)          | 4100S          | 4100ST                          |
| 1-1/4               | 44.5 (1.75) | 42.9 (1.69)      | 14.2 (0.56)   | 19.05 (42.00)          | 4125S          | 4125ST                          |
| 1-1/2               | 49.3 (1.94) | 49.3 (1.94)      | 14.2 (0.56)   | 24.04 (53.00)          | 4150S          | 4150ST                          |
| 2                   | 55.6 (2.19) | 60.5 (2.38)      | 16.0 (0.63)   | 34.02 (75.00)          | 4200S          | 4200ST                          |
| 2 - 1/2             | 60.5 (2.38) | 79.5 (3.13)      | 22.4 (0.88)   | 58.97 (130.00)         | 4250S          | 4250ST                          |
| 3                   | 73.2 (2.88) | 95.3 (3.75)      | 22.4 (0.88)   | 104.33(230.00)         | 4300S          | 4300ST                          |
| 3 - 1/2             | 76.2 (3.00) | 108.0 (4.25)     | 25.4 (1.00)   | 113.40 (250.00)        | 4350S          | 4350ST                          |
| 4                   | 81.0 (3.19) | 120.7 (4.75)     | 25.4 (1.00)   | 113.40 (250.00)        | 4400S          | 4400ST                          |

# ETP™ 4000S Series Steel EMT Set Screw Connectors

NEC/CEC:  
Listed for Ordinary Locations

## Application

- To ground and secure EMT raceways to boxes and enclosures.

## Features


- Heavy steel walls.
- Concretetight when taped.
- Pre-set/pre-staked set screws.
- Male hub threads — NPS.
- Available with insulated throat.
- Three-way combination screws 1/2" thru 2".
- Slotted hexhead screw 2-1/2" thru 4".
- Insulated throat connector rated +90 °C (+194 °F).
- 2-1/2" thru 4" rated for threadless Aluminum RMC and steel IMC.

## Materials/Finish

- Steel/zinc plated

## NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E-14895
- CSA Certified: 028507
- NEMA: FB-1



4050S-4100S



4125S - 4400S

Dimensions in Millimeters (Inches)

| Trade Size (Inches) | Body Length | Maximum Diameter | Thread Length | Weight per 100 kg (lb) | Catalog Number | Insulated Throat Catalog Number |
|---------------------|-------------|------------------|---------------|------------------------|----------------|---------------------------------|
| 1/2                 | 26.2 (1.03) | 21.3 (0.84)      | 11.2 (0.44)   | 4.54 (10.00)           | 4050S          | 4050ST                          |
| 3/4                 | 27.7 (1.09) | 27.4 (1.08)      | 11.2 (0.44)   | 6.80 (15.00)           | 4075S          | 4075ST                          |
| 1                   | 30.2 (1.19) | 33.3 (1.31)      | 11.2 (0.44)   | 10.43 (23.00)          | 4100S          | 4100ST                          |
| 1-1/4               | 44.5 (1.75) | 42.9 (1.69)      | 14.2 (0.56)   | 19.05 (42.00)          | 4125S          | 4125ST                          |
| 1-1/2               | 49.3 (1.94) | 49.3 (1.94)      | 14.2 (0.56)   | 24.04 (53.00)          | 4150S          | 4150ST                          |
| 2                   | 55.6 (2.19) | 60.5 (2.38)      | 16.0 (0.63)   | 34.02 (75.00)          | 4200S          | 4200ST                          |
| 2 - 1/2             | 60.5 (2.38) | 79.5 (3.13)      | 22.4 (0.88)   | 58.97 (130.00)         | 4250S          | 4250ST                          |
| 3                   | 73.2 (2.88) | 95.3 (3.75)      | 22.4 (0.88)   | 104.33(230.00)         | 4300S          | 4300ST                          |
| 3 - 1/2             | 76.2 (3.00) | 108.0 (4.25)     | 25.4 (1.00)   | 113.40 (250.00)        | 4350S          | 4350ST                          |
| 4                   | 81.0 (3.19) | 120.7 (4.75)     | 25.4 (1.00)   | 113.40 (250.00)        | 4400S          | 4400ST                          |