

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Uses, Certifications, and Standards

standard

## **455 2" Ground Bushing Lay-In Lug**Arlington Industries

Arlington Industries
2" Insulated Metal Grounding Bushing. Threaded. C-Clamp Grounding Lug Is Dual Rated For Copper and Aluminum. Made Of Zinc Die-Cast, It Is Rated For 150 Degree C. Minimum Size Ground Is 14 Gauge and Max Wire Size Is 2 Gauge.
0.1800 (lbs/each)
Rigid Conduit Fittings - Steel
Zinc
ZIIIC
2.404
3.604
L(3.604) x W(2.665) x H(1.385)
2" GROUND BUSHING LAY-IN LUG
ARL 455 2" GRD.BUSH.LAY-IN LUG
2" insulated metal grounding bushing. Threaded. C-clamp grounding lug is dual rated for copper and aluminum. Made of zinc die-cast, it is rated for 150 Degree C. Minimum size ground is 14 gauge and max wire size is 2 gauge.
2" GRD.Bush.Lay-In Lug
Dual rated CU-AL C-clamp grounding lug
Arlington Industries
00018997004550
018997004550
gories
SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding Fittings & Ground Rods
Threaded Bushing
10
50
0.18

**UL and CSA**