



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



5237UL Photo Sensor *Nsi Industries*

| | |
|------------------|-------------------------------------|
| Catalog Number | 5237UL |
| Manufacturer | Nsi Industries |
| Description | Turnlock Led Electronic 105-305V Ir |
| Weight per unit | 0.2700 (lbs/each) |
| Product Category | Lighting Occupancy Sensors |

Features

| | |
|----------------|------------------|
| supply voltage | 105-305 VAC |
| Timing Range | 3-5 Second Delay |

Dimensions and Weight

| | |
|------|-------------------|
| Size | H=2.187 - W=3.187 |
|------|-------------------|

Descriptions

| | |
|------------------------|--|
| Description | PHOTO SENSOR |
| extra long description | TORK 5237-UL TurnLock LED Electroni |
| Features | Electronic Instant Response TurnLock, On 1.3-1.7, Off/On Ratio 1.5:1, 105-305V, 1000W Tungsten, 1800VA Ballast,1000W LED |
| Long Description | TurnLock LED Electronic 105-305V IR |
| Product Type | Turnlock Led Electronic 105-305V Ir |
| Special Features | 360 Joule MOV (Metal Oxide Varistor) Surge Arrestor - Locking Prongs - Silicon Photosensor |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | NSi |
| GTIN | 00786261788955 |
| Manufacturers Part Number | 5237-UL |
| UPC | 786261788955 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | Commercial dimmers, motion sensors, & photo cells |
| Type | Utility Grade Electronic With Fail On Mode |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Weight Per each | 0.27 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

| | |
|--------------------------|---|
| Application | Local Utility-Street-Highway Lighting Control |
| Enclosure | Polycarbonate |
| environmental conditions | -40 to + 158 F |
| Frequency Rating | 50-60 Hz |
| Mounting | TWIST LOCK |
| Operating Temperature | -40 to + 158 F |
| standard | UL |