



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 5641 5641 Term Kit *Minnesota Mining (3M)*

|                  |   |
|------------------|---|
| Catalog Number   | 5641  |
| Manufacturer     | Minnesota Mining (3M)   |
| Description      | 3M™ Cold Shrink QT II 5640 & 5650 Series Termination Kit Includes A 4 Skirt, 1 Piece Termination. It Ensures A Pliable, Tight Seal For Jacketed Concentric Neutral Power Cables. The Conjunction Of High Dielectric Constant Material and Silicone Rubber Insulation Allows The Termination to Withstand Voltages Up to 15KV. |
| Weight per unit  | 0.7780 (lbs/each)   |
| Product Category | Splicing & Terminating Kits   |

### Descriptions

|                        |   |
|------------------------|---|
| Description            | 5641 TERM KIT   |
| extra long description | 3M 7000057844 3M™ Cold Shrink QT-II   |
| Long Description       | 3M™ Cold Shrink QT II 5640 & 5650 Series Termination Kit includes a 4 skirt, 1 piece termination. It ensures a pliable, tight seal for jacketed concentric neutral power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages up to 15kV. |
| Product Type           | 3M™ Cold Shrink QT-II Outdoor Termination Kits 5640 & 5650 S  |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | 3M             |
| GTIN                      | 00054007119630 |
| Manufacturers Part Number | 5641           |
| UPC                       | 054007119630   |

### Taxonomies, Classifications, and Categories

|                      |           |
|----------------------|-----------|
| Category Description | TERMINALS |
| Type                 | QT-II     |

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Weight Per each | 0.778 |

### Uses, Certifications, and Standards

|             |         |
|-------------|---------|
| Application | Outdoor |
| standard    | IEEE    |