

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **65033000 3/4" LFNC Orange Sealtite** *Southwire Company*

Catalog Number	65033000
Manufacturer	Southwire Company
Description	Liquid Tight Sealtite, Orange Color, Made In Usa, 6503 Model/Series, LFNC Style, 3/4 In Trade Size, 0.18 LB/FT Weight
Weight per unit	0.1800 (lbs/ft)
Product Category	Liquid Tight Conduit
Features	
Inside Diameter	0.805/0.845
Material	PVC
outside diameter	1.140/1.180
Material, Color, and Finish	
Finish	PVC
Jacket Material	PVC
<b>Dimensions and Weight</b>	
Length	100
Descriptions	
Description	3/4" LFNC ORANGE SEALTITE
extra long description	AFC 6503-30-00 3/4 UL ORANGE LFNC-A
Features	LIQUID-TUFF™ Type LFNC-A is a layered Liquidtight Flexible Nonmetallic Conduit, designed for use in wet, dry or oily locations as a flame resistant, Nonmetallic raceway for power, control and communications cables where repetitive motion and constant flexing is required. It is intended for applications where abrasion and physical abuse may occur. LIQUID-TUFF™ Type LFNC-A carries the UL Listing Marks for US and Canada
Special Features	Nylon reinforced braid between two layers of PVC for strength and flexibility. Sunlight resistant, oil resistant, mild acid resistance, non-conductive raceway.
Manufacturer Information	
Brand	Flexible Conduit

#### M

Brand	Flexible Conduit
GTIN	00077680175724
Manufacturers Part Number	6503-30-00
UPC	077680175724

### **Taxonomies, Classifications, and Categories**

Category Description	Liquid Tight
Type	Liquidtight Flexible Non-Metallic Conduit



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per foot	0.18
Uses, Certifications, and Standa	
Application	Constant flexing and motion applications
standard	UL 1660 E123464
Temperature Rating	176
	Constant flexing and motion applications UL 1660 E123464 176