

## Sign & scoreboard lighting

### Product description

Attachon lampholders,  
660W, 250V/AC; 200W, 250V/AC

### Features

- Insulation displacement terminals for stranded wire
- Lay in wire channels, 1/4 turn twist top speeds installation
- One piece terminals and contacts, no rivets or eyelets to loosen due to heat
- Sockets are molded of heat-resistant phenolic
- #732 is weatherproof, suitable for outdoor use
- Intermediate and candelabra bases offer snap-in or screw-in panel mounting options
- Keyed spring washer prevents rotation of socket after installation





732



732-3

### Medium base Attachon

| Rating |      | Description  | Catalog no. |  |  |
|--------|------|--|-------------|---|---|
| W      | V/AC |  |             |   |   |
| 660    | 250  | Weatherproof phenolic, wire range #14 to #12 AWG, hook mounting    | □ 732       | •   | •   |
|        |      | Weatherproof phenolic, wire range #14 to #12 AWG, no hook mounting | □ 732-1     | •   | •   |
|        |      | Weatherproof phenolic, wire range #14 to #12 AWG, snap-in mounting | □ 732-3     | •   | •   |

For panel cutout dimensional data, see Section Q-Technical Reference

### Medium base Attachon with guard

| Rating |      | Description   | Catalog no. |  |  |
|--------|------|---|-------------|---|---|
| W      | V/AC |   |             |   |   |
| 200    | 250  | Phenolic socket (732), yellow guard, wire range #18 to #12 AWG, hook mounting | □ 1466Y     | •   | •   |

Compliances, specifications and availability are subject to change without notice.

 Indicates NAFTA compliant - Page Q-32

 RoHS compliant - Page Q-32

## Sign & scoreboard lighting

### Product description

Attachon lampholders,  
660W, 250V/AC; 200W, 250V/AC

### Features

- Insulation displacement terminals for stranded wire
- Lay in wire channels, 1/4 turn twist top speeds installation
- One piece terminals and contacts, no rivets or eyelets to loosen due to heat
- Sockets are molded of heat-resistant phenolic
- #732 is weatherproof, suitable for outdoor use
- Intermediate and candelabra bases offer snap-in or screw-in panel mounting options
- Keyed spring washer prevents rotation of socket after installation





732



732-3

### Medium base Attachon

| Rating |      | Description  | Catalog no. |  |  |
|--------|------|--|-------------|---|---|
| W      | V/AC |  |             |   |   |
| 660    | 250  | Weatherproof phenolic, wire range #14 to #12 AWG, hook mounting    | □ 732       | •   | •   |
|        |      | Weatherproof phenolic, wire range #14 to #12 AWG, no hook mounting | □ 732-1     | •   | •   |
|        |      | Weatherproof phenolic, wire range #14 to #12 AWG, snap-in mounting | □ 732-3     | •   | •   |

For panel cutout dimensional data, see Section Q-Technical Reference

### Medium base Attachon with guard

| Rating |      | Description   | Catalog no. |  |  |
|--------|------|---|-------------|---|---|
| W      | V/AC |   |             |   |   |
| 200    | 250  | Phenolic socket (732), yellow guard, wire range #18 to #12 AWG, hook mounting | □ 1466Y     | •   | •   |

Compliances, specifications and availability are subject to change without notice.

 Indicates NAFTA compliant - Page Q-32

 RoHS compliant - Page Q-32