



**Product Number:** 16751

**Order Abbreviation:** 80PAR38/HAL/S/WFL50 120V

**General Description:** Tungsten Halogen PAR38 Reflector Lamp 80Watt 120Volt Medium Skirted Base WideFlood50 Beam

**\* Full Case Required**

#### Product Information

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Abbrev. With Packaging Info.      | 80PAR38HALSWFL50 120V 10/CS 1/SKU |
| Approx. Lumens                    | 1545                              |
| Average Rated Life (hr)           | 1500                              |
| Base                              | E26 Medium Skirted                |
| Beam Angle (deg)                  | 50                                |
| Beam Type                         | WFL                               |
| Bulb                              | PAR38                             |
| Centerbeam Candlepower (cp)       | 2300                              |
| Class                             | YES                               |
| Color Rendering Index (CRI)       | 99                                |
| Color Temperature/CCT (K)         | 2950                              |
| Diameter (in)                     | 4.752                             |
| Diameter (mm)                     | 120.70                            |
| Family Brand Name                 | CAPSYLITE® PAR38                  |
| Filament                          | CC-8                              |
| Horizontal Beam Angle (deg)       | 50                                |
| Lamp Finish                       | Reflector                         |
| Maximum Overall Length - MOL (in) | 5.313                             |
| Maximum Overall Length - MOL (mm) | 134.9375                          |
| Nominal Voltage (V)               | 120.00                            |
| Nominal Wattage (W)               | 80.00                             |
| Vertical Beam Angle (deg)         | 50                                |



#### Footnotes

- State of the Art SPL Optics
- To avoid electric shock and/or skin burns, turn off power and allow bulb to cool before handling or attempting replacement.
- In base up operation, heat may eventually deteriorate paper-lined or plastic sockets.



**Product Number:** 16751

**Order Abbreviation:** 80PAR38/HAL/S/WFL50 120V

**General Description:** Tungsten Halogen PAR38 Reflector Lamp 80Watt 120Volt Medium Skirted Base WideFlood50 Beam

**\* Full Case Required**

#### Product Information

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Abbrev. With Packaging Info.      | 80PAR38HALSWFL50 120V 10/CS 1/SKU |
| Approx. Lumens                    | 1545                              |
| Average Rated Life (hr)           | 1500                              |
| Base                              | E26 Medium Skirted                |
| Beam Angle (deg)                  | 50                                |
| Beam Type                         | WFL                               |
| Bulb                              | PAR38                             |
| Centerbeam Candlepower (cp)       | 2300                              |
| Class                             | YES                               |
| Color Rendering Index (CRI)       | 99                                |
| Color Temperature/CCT (K)         | 2950                              |
| Diameter (in)                     | 4.752                             |
| Diameter (mm)                     | 120.70                            |
| Family Brand Name                 | CAPSYLITE® PAR38                  |
| Filament                          | CC-8                              |
| Horizontal Beam Angle (deg)       | 50                                |
| Lamp Finish                       | Reflector                         |
| Maximum Overall Length - MOL (in) | 5.313                             |
| Maximum Overall Length - MOL (mm) | 134.9375                          |
| Nominal Voltage (V)               | 120.00                            |
| Nominal Wattage (W)               | 80.00                             |
| Vertical Beam Angle (deg)         | 50                                |



#### Footnotes

- State of the Art SPL Optics
- To avoid electric shock and/or skin burns, turn off power and allow bulb to cool before handling or attempting replacement.
- In base up operation, heat may eventually deteriorate paper-lined or plastic sockets.