

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## **850A 3/8" 90D Flex Conn** *Arlington Industries*

850A
Arlington Industries
Zinc Die-Cast, 90 Degree 2 Screw Flex Connector For Aluminum and Steel Flex. Secures Into A 1/2" Knockout With A Diecast Locknut. Accommodates Cable Range .635 to 1.085. Insulated Throat.
0.0600 (lbs/each)
Liquid Tight Fittings
Threaded X Screw
Zinc
Silver
L(1.800) x W(1.432) x H(0.750)
3/8" 90D FLEX CONN
ARL 850A INS. 3/8" 90 FLEX CONN
Zinc die-cast, 90 degree 2 screw flex connector for aluminum and steel Flex. Secures into a 1/2" Knockout with a diecast locknut.  Accommodates cable range .635 to 1.085. Insulated Throat.
Ins. 3/8" 90 Flex Conn
Concrete tight when taped
ARLINGTON
00018997850102
850A
018997850102
Categories
FLEX & MC FITTINGS
90 DEG Connector
50
500

0.06

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	For AC - MCI-A - HCF steel and aluminum cable
standard	CULUS and CSA