

# A75-30-11 110V 50Hz / 110-120V 60Hz

ABB contact for Canada [Print/View..](#)  
[Print to Pdf..](#)

## General Information

<b>Extended Product Type:</b>	A75-30-11 110V 50Hz / 110-120V 60Hz
<b>Product ID:</b>	1SBL411001R8411
<b>EAN:</b>	3471522093844
<b>Catalog Description:</b>	A75-30-11 110V 50Hz / 110-120V 60Hz Contactor
<b>Long Description:</b>	A75 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC / 1000 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles and 2 built-in auxiliary contacts, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.



## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

<b>EAN:</b>	3471522093844
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369085

## Dimensions

<b>Product Net Width:</b>	82.0 mm
<b>Product Net Depth:</b>	108.0 mm
<b>Product Net Height:</b>	110.0 mm
<b>Product Net Weight:</b>	1.200 kg

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	140 mm
<b>Package Level 1 Length:</b>	146 mm
<b>Package Level 1 Height:</b>	96 mm
<b>Package Level 1 Gross Weight:</b>	1.20000 kg
<b>Package Level 1 EAN:</b>	3471522093844
<b>Package Level 2 Units:</b>	20 piece
<b>Package Level 3 Units:</b>	160 piece

## Environmental

<b>Ambient Air Temperature:</b>	Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 °C Close to Contactor for Storage -60 ... +80 °C Close to Contactor without Thermal O/L Relay (0.85 - 1.1 U <sub>c</sub> ) -40 ... +55 °C Close to Contactor without Thermal O/L Relay (U <sub>c</sub> ) -40 ... +70 °C
<b>Maximum Operating Altitude Permissible:</b>	3000 m
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical

<b>Rated Operational Power AC-3 (P<sub>e</sub>):</b>	(220 / 230 / 240V) 22 kW (380 / 400V) 37 kW (415V) 40 kW (440V) 40 kW (500V) 45 kW (690V) 40 kW
<b>Rated Operational Current AC-1 (I<sub>e</sub>):</b>	(690V) 40°C 125 A (690V) 55°C 105 A (690V) 70°C 85 A
<b>Number of Main Contacts NO:</b>	3
<b>Number of Main Contacts NC:</b>	0
<b>Number of Auxiliary Contacts NO:</b>	1
<b>Number of Auxiliary Contacts NC:</b>	1
<b>Rated Control Circuit Voltage (U<sub>c</sub>):</b>	50 Hz 110 V 60 Hz 110 ... 120 V
<b>Terminal Type:</b>	Screw Terminals
<b>Coil Consumption:</b>	Average Holding Value 50/60Hz 18 V·A Average Holding Value 50/60Hz 5.5 W Average Pull-in Value 50Hz 190 V·A Average Pull-in Value 60Hz 180 V·A

## Certificates and Declarations (Document Number)

<b>ASEFA Certificate:</b>	ASEFA_15201
<b>BV Certificate:</b>	BV_2634H07559D0
<b>CB Certificate:</b>	CB_FR_602227A
<b>CCC Certificate:</b>	CCC_2002010304016447
<b>CSA Certificate:</b>	CSA_1033838_LR056745
<b>cUL Certificate:</b>	UL_071301E39231
<b>Declaration of Conformity - CE:</b>	1SBD250803C3000
<b>DNV Certificate:</b>	DNV_E12025
<b>EAC Certificate:</b>	EAC_RU C-FR ME77 B01010
<b>GL Certificate:</b>	GL_9949997HH
<b>GOST Certificate:</b>	GOST_POCCFRME77B07175
<b>LOVAG Certificate:</b>	LOVAG_FR01006a-FR01030
<b>LR Certificate:</b>	LRS_9830011E2
<b>RINA Certificate:</b>	RINA_ELE128713XG001
<b>RMRS Certificate:</b>	RMRS_0507015250
<b>RoHS Information:</b>	1SBD350061R1000
<b>UL Certificate:</b>	UL_071301E39231

# A75-30-11 110V 50Hz / 110-120V 60Hz

ABB contact for Canada [Print/View..](#)  
[Print to Pdf..](#)

## General Information

<b>Extended Product Type:</b>	A75-30-11 110V 50Hz / 110-120V 60Hz
<b>Product ID:</b>	1SBL411001R8411
<b>EAN:</b>	3471522093844
<b>Catalog Description:</b>	A75-30-11 110V 50Hz / 110-120V 60Hz Contactor
<b>Long Description:</b>	A75 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC / 1000 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles and 2 built-in auxiliary contacts, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.



## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

<b>EAN:</b>	3471522093844
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369085

## Dimensions

<b>Product Net Width:</b>	82.0 mm
<b>Product Net Depth:</b>	108.0 mm
<b>Product Net Height:</b>	110.0 mm
<b>Product Net Weight:</b>	1.200 kg

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	140 mm
<b>Package Level 1 Length:</b>	146 mm
<b>Package Level 1 Height:</b>	96 mm
<b>Package Level 1 Gross Weight:</b>	1.20000 kg
<b>Package Level 1 EAN:</b>	3471522093844
<b>Package Level 2 Units:</b>	20 piece
<b>Package Level 3 Units:</b>	160 piece

## Environmental

<b>Ambient Air Temperature:</b>	Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 °C Close to Contactor for Storage -60 ... +80 °C Close to Contactor without Thermal O/L Relay (0.85 - 1.1 U <sub>c</sub> ) -40 ... +55 °C Close to Contactor without Thermal O/L Relay (U <sub>c</sub> ) -40 ... +70 °C
<b>Maximum Operating Altitude Permissible:</b>	3000 m
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical

<b>Rated Operational Power AC-3 (P<sub>e</sub>):</b>	(220 / 230 / 240V) 22 kW (380 / 400V) 37 kW (415V) 40 kW (440V) 40 kW (500V) 45 kW (690V) 40 kW
<b>Rated Operational Current AC-1 (I<sub>e</sub>):</b>	(690V) 40°C 125 A (690V) 55°C 105 A (690V) 70°C 85 A
<b>Number of Main Contacts NO:</b>	3
<b>Number of Main Contacts NC:</b>	0
<b>Number of Auxiliary Contacts NO:</b>	1
<b>Number of Auxiliary Contacts NC:</b>	1
<b>Rated Control Circuit Voltage (U<sub>c</sub>):</b>	50 Hz 110 V 60 Hz 110 ... 120 V
<b>Terminal Type:</b>	Screw Terminals
<b>Coil Consumption:</b>	Average Holding Value 50/60Hz 18 V·A Average Holding Value 50/60Hz 5.5 W Average Pull-in Value 50Hz 190 V·A Average Pull-in Value 60Hz 180 V·A

## Certificates and Declarations (Document Number)

<b>ASEFA Certificate:</b>	ASEFA_15201
<b>BV Certificate:</b>	BV_2634H07559D0
<b>CB Certificate:</b>	CB_FR_602227A
<b>CCC Certificate:</b>	CCC_2002010304016447
<b>CSA Certificate:</b>	CSA_1033838_LR056745
<b>cUL Certificate:</b>	UL_071301E39231
<b>Declaration of Conformity - CE:</b>	1SBD250803C3000
<b>DNV Certificate:</b>	DNV_E12025
<b>EAC Certificate:</b>	EAC_RU C-FR ME77 B01010
<b>GL Certificate:</b>	GL_9949997HH
<b>GOST Certificate:</b>	GOST_POCCFRME77B07175
<b>LOVAG Certificate:</b>	LOVAG_FR01006a-FR01030
<b>LR Certificate:</b>	LRS_9830011E2
<b>RINA Certificate:</b>	RINA_ELE128713XG001
<b>RMRS Certificate:</b>	RMRS_0507015250
<b>RoHS Information:</b>	1SBD350061R1000
<b>UL Certificate:</b>	UL_071301E39231