

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



ABC15R 15A 250V 1/4X1-1/4 Fa Ceramic Fuse Bussmann Fuses

Catalog Number	ABC15R
Manufacturer	Bussmann Fuses
Description	Eaton GBB Series Very Fast-Acting Fuse, 6A, 250 Vac, 125 VDC, R
Weight per unit	0.0100 (lbs/each)
Product Category	Small Dimension Fuses
turos	

Features

10.100	
amperage rating	15 A
connection	Ferrule End X Ferrule End
dimensions	X X 1.2598 IN
interrupt rating	10 kAIC at 125 Vac/dc750 AIC at 250 Vac
Material	Nickel-plated brass endcapsCeramic tube
Response Time	4 hr at 100%, 60 min at 135%, 120 sec at 200%
type of indicators	Non-Indicating
Voltage Rating	250 Vac, 125 Vdc, 32 Vac (self certified)
	·

Dimensions and Weight

9	
Size	1/4 In Diameter X 1-1/4 In Length

Descriptions

15A 250V 1/4X1-1/4 FA CERAMIC FUSE
EFSE ABC-15-R BUSS SMALL DIMENSION
Fast-acting, ceramic tube 1/4" x 1-1/4" ferrule fuse designed to UL 248-14 for overcurrent protection of electronic circuits. Install into a Bussmann Series fuse holder, block, or fuse clip, or purchase with available axial leads for thru-hole installation. Eaton's ABC fast-acting, ceramic body tube 1/4" x 1-1/4" fuses are designed with higher interrupting ratings and voltage ratings to UL 248-14 for overcurrent protection of electronic circuits. This is a RoHS compliant fuse. Order in cartridge fuse form
Eaton GBB Series Very fast-acting fuse, 6A, 250 Vac, 125 Vdc, R
Buss Small Dimension Fuse
Interrupt Rating 750 Amp at 250 Vac, 10000 Amp at 125 Vac/Vdc, Material Ceramic Tube, Nickel Plated Brass Endcap, ROHS Compliant

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712646192
Manufacturers Part Number	ABC-15-R
UPC	051712646192



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	GLASS FUSES (and ceramic)
Туре	Fast-Acting Fuse
Packaging Carton	
Carton	5
Weight Per each	0.01
Uses, Certifications, and Standards Application	Ind Facilities & Factories - Facility: Safety and Security Systems

CE Marked, RoHS Compliant