

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## AF96301114 92A, 250-500V, 3P Contactor

Industrial Connections of Catalog Number	AF96301114
Manufacturer	Industrial Connections &
Description	AF96 Contactors Are Used For Controlling Power Circuits Up to 690 V Ac and 220 V DC. They Are Mainly Used For Controlling 3-Phase Motors, Non-Inductive or Slightly Inductive Loads. Af Contactors Include An Electronic Coil Interface Accepting A Wide Control Voltage Uc Min Uc Max. Only Four Coils Cover Control Voltages Between 24500 V 50/60 HZ or 20500 V DC. Af Contactors Can Manage Large Control Voltage Variations. One
	Coil Can Be Used For Different Control Voltages Used Worldwide Without Any
Weight per unit	3.0 (lbs/each)
Product Category	IEC Contactors
Descriptions	
Description	92A, 250-500V, 3P CONTACTOR
extra long description	ABB AF96-30-11-14 CTR,3P,92A,250-50
Long Description	AF96 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF contactors include an electronic coil interface accepting a wide control voltage Uc min Uc max. Only four coils cover control voltages between 24500 V 50/60 Hz or 20500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any
Product Type	CTR, 3P, 92A, 250-500VAC/DC, 1/1
Manufacturer Information	
Brand	ABB
GTIN	00888614131606
	AF96-30-11-14
UPC	888614131606
Taxonomies, Classifications, and Category Description	Categories IEC/FREEDOM CONTACTOR
Packaging	
Carton	1
Package	54
14/ 1 1 . 5	

2.96