


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





## ATD1000CRP Adt Occsens, CLG MT, 1000 SQ FT W/R Hubbell Wiring Devices

Soon	
Catalog Number	ATD1000CRP
Manufacturer	Hubbell Wiring Devices
Description	Switches and Lighting Controls, Occupancy Sensors, Adaptive
	Dual-Technology Ceiling Sensor, 1000 Square Feet Coverage,
	With Relay
Weight per unit	
Product Category	Lighting Occupancy Sensors
itures	
connector	Wire Leads
indicator	PIR= Red LED, Ultrasonic= Green LED
load	Load is a function of the control unit
operating cycles	6,000
pallet quantity	840
supply voltage	24V DC From Control Unit
Voltage Rating	24
terial, Color, and Finish	
Color	White
scriptions	
Description	ADT OCCSENS, CLG MT, 1000 SQ FT W/R
extra long description	HWDK ATD1000CRP ADT OCCSENS, CLG MT
Features	Adaptive Dual Technology combines Ultrasonic and Passive Infrared technology, minimizing the risk of lights turning ON when the space is unoccupied. Once occupancy is detected by both technologies within the space lights are turned ON, only one technology is necessary to keep the lights ON. Adaptive technology provides better control. Hubbell's patented breakthrough in advanced control feature smart microprocessor constantly monitoring the controlled area and adjust the sensitivity and timer based on envi
Long Description	Switches and Lighting Controls, Occupancy Sensors, Adaptive Dual-Technology Ceiling Sensor, 1000 Square Feet Coverage,
	With Relay
Product Type	



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

**Manufacturer Information** 

Brand	Hubbell Wiring Device-Kellems
GTIN	00783585392417
Manufacturers Part Number	ATD1000CRP
series	Accessories;Dual
UPC	783585392417

**Taxonomies, Classifications, and Categories** 

Category Description	Residential dimmers, motion sensors, controls, & photo cells
Туре	Sensors
Packaging Carton	1
Package	10
Weight Per each	0.7

Uses, Certifications, and Standards

Application	Compatible with most LED and CFL
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Ceiling mount
standard	ASHRAE 90.1 Compliant; cULus Listed To UL244A