

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

AYCL153PHLA Ariadni 150W Led 3WAY Light Almond Clam *Lutron*

| O Labor Navalana | AVOL4FODLILA |
|---------------------------------|---|
| Catalog Number | AYCL153PHLA |
| Manufacturer Description | Lutron Dimmable Bulb, Toggle Switch Type, 120 V, 150 W;6000 W, 60 HZ, Incandescent/Halogen;Dimmable CFL/Led Lamp, Motion Sensor, Wall Mount, 2.86 In Length, 2.58 In Width, 4.60 In |
| | Height, Light Almond, +32 °F Operating Temperature, +104 °F Operating Temperature, 1 Yr Warranty, 0.4 LB/Ea |
| Weight per unit | 0.4000 (lbs/each) |
| Product Category | Lighting Dimmers |
| Features | |
| actuator | Toggle Switch |
| connection | Screw Terminal |
| Connection Type | Screw Terminal |
| insulation | Plastic |
| Material | Plastic/Metal |
| Poles | 1 |
| Voltage Rating | 120 |
| Wattage | 600 |
| Material, Color, and Finish | |
| Finish | Gloss |
| Dimensions and Weight | |
| Size | 4.60 x 2.86;117 x 73 |
| Descriptions | |
| Description | ARIADNI 150W LED 3WAY LIGHT ALMOND CLAM |
| extra long description | LUT AYCL-153PH-LA ARIADNI CFL/LED D |
| Special Features | Controls 150 W LED/CFL (screw-base) or 600 W |
| · | incandescent/halogen loads. Toggle turn lights on/off. Slide up to |
| | brighten, down to dim. Provides reliable dimming of dimmable |
| | LEDs/CFLs as well as halogens and incandescents. |
| Manufacturer Information | |
| GTIN | 00027557826037 |
| UPC | 027557826037 |
| Taxonomies, Classifications, an | d Categories |
| 0.1 D!.! | Residential dimmers, motion sensors, controls, & photo cells |
| T | December 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 |

Preset dimmer, 3-way/single-pole, clamshell packaging



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging | | | | | |
|-----------|-----|----|----|---|---|
| | Pac | ka | gı | n | g |

| Carton | 1 | |
|-----------------|-----|--|
| Package | 48 | |
| Weight Per each | 0.4 | |

Uses, Certifications, and Standards

| Application | Lighting Control | |
|--------------------------|-----------------------------|--|
| Enclosure | Plastic | |
| environmental conditions | Indoor use only | |
| Mounting | WALLBOX | |
| Operating Temperature | 32 to 104 | |
| standard | UL1472 CSA C22.2 184.1, NOM | |