

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **B21** B-Cap Wire Connector, Model B2 Red, 100/Box Ideal

Catalog Number	B21
Manufacturer	Ideal
Description	Wire Connector, (2) #18 Awg Conductor Size, (5) #12 Awg Conductor Size, Red Insulation Color, +221 °F Operating Temperature, 2 to 6 Conductors, 600 V Ac, 0.01 LB
Weight per unit	0.0080 (lbs/each)
Product Category	Electrical Fixture Conn ( Nuts
3	
Features Material	Flamo rotardant Polypropologo
Voltage Rating	Flame-retardant Polypropelene 600
Ţ	000
Material, Color, and Finish	
Color	Red
Descriptions	
Description	B-CAP WIRE CONNECTOR, MODEL B2 RED, 100/BOX
extra long description	IDEAL B2-1 B-CAP B2 RED, 100 BOX
Features	The B-CAP Wire Connector gets you in those hard-to reach spots comfortably, especially when you're retrofitting or updating. Slim, classic fins and an expanding interior spring give the B-CAP a secure grip with extra leverage, making it the most compact connector on the market for up to 5 #12 (Red Model B2). The unique, space-saving profile of the B-CAP makes it perfect for retrofit work and shallow boxes. The B-CAP also features a tough flame-retardant shell that withstands environmental extremes with a de
Manufacturer Information	
Brand	Buchanan
GTIN	00781789451879
UPC	781789451879
Taxonomies, Classifications, and Category Description	I Categories  Datacom Wiring Devices and Accessories
Availability	
minimum qty	100
Packaging	
Carton	100
Package	1000
Weight Per cap	0.008
aroigine i oi oup	2.444

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	Insulating or Joining 1 or more conductors
environmental conditions	Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221
	F)
standard	CSA C22.2 #188, UL 486C Listed, RoHS