



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## BG48SA 1" to 1-1/4" Alu BLNK MGL CVR

*Crouse-Hinds*

Catalog Number	BG48SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet B Mogul Blank Cover, Copper-Free Aluminum, Round Neoprene Gasket, 1" or 1-1/4"
Weight per unit	0.5900 (lbs/each)
Product Category	Alum

### Features

dimensions	2.1900 IN X 1.4600 IN X 8.0000 IN
------------	-----------------------------------

### Descriptions

Description	1" TO 1-1/4" ALU BLNK MGL CVR
extra long description	CRS-H BG48 SA 1 OR 1 1/4 CST AL MOG
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet B mogul blank cover, Copper-free aluminum, Round neoprene gasket, 1" or 1-1/4"
Product Type	1 or 1 1/4 CST Al Mogul CVR/Gask

### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274126876
Manufacturers Part Number	BG48 SA
UPC	782274126876

### Taxonomies, Classifications, and Categories

Category Description	Form 9 condulets, covers & gaskets
Type	Mogul blank cover

### Packaging

Carton	1
Package	5
Weight Per each	0.59



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

---

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D