

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BG68 1-1/2" to 2" Body CVR&GSKT Crouse-Hinds

Catalog Number	BG68
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet B Mogul Blank Cover,
	Feraloy Iron Alloy, Round Neoprene Gasket, 1-1/2" or 2"
Weight per unit	5.9 (lbs/each)
Product Category	Bodies & Covers
Features	
Material	FERALOY IRON ALLOY
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight Height	12.19
Length	3.56
Width	1.46
	1.70
Descriptions	
Description	1-1/2" TO 2" BODY CVR&GSKT
extra long description Features	CRS-H BG68 1 1/2 OR 2 IRON MOGUL CV Crouse-Hinds series mogul bodies are installed in conduit
	systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet B mogul blank cover, Feraloy iron alloy, Round neoprene gasket, 1-1/2" or 2"
Product Type	1 1/2 or 2 Iron Mogul CVP/Cask
Special Features	Round neoprene gasket
Manufacturer Information	
Brand	Eaton
GTIN	00782274101903
Manufacturers Part Number	BG68
UPC	782274101903
Taxonomies, Classifications, and (Categories
Category Description	
Туре	Mogul blank cover



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	
Package	2
Weight Per each	5.9

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D