


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





series UPC

BR20I RCPT, Dup SB, Com GRD, 20A 125V, B/S, Iv Hubbell Wiring Devices

Catalog Number	BR20I
Manufacturer	Hubball Wiring Davicas
Description	Straight Blade Devices, Receptacles, Duplex, Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Ivory, Single Pack.
Weight per unit	0.1900 (lbs/each)
Product Category	
eatures	
amperage rating	20
connection	Back and Side Wired
Current Rating	
Dielectric Strength	Withstands 2,000V minimum
Material	Nylon
Number of Wires	3-Wire
pallet quantity	
Phase	1
Poles	2-Pole
Voltage Rating	125 V
Wattage	2,500
Wire Size	#12 to #10
imensions and Weight	
Size	1.32 in x 0.83 in x 3.28 in
escriptions	
Description	RCPT, DUP SB, COM GRD, 20A 125V, B/S, IV
extra long description	HWDK BR20I RCPT, DUP SB, COM GRD, 2
Long Description	Straight Blade Devices, Receptacles, Duplex,
	Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 20A
	125V, 5-20R, Ivory, Single Pack.
Product Type	RCPT, Dup SB, Com GRD, 20A 125V, B/S, Iv
Special Features	Self Grounding
lanufacturer Information	
Brand	WIRING DEVICE-KELLEMS
GTIN	00783585834887
Manufacturers Part Number	BR20I
series	Commercial Specification Grade

783585834887



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

0.19

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies	, Classifications,	and Categories
-------------------	--------------------	----------------

Category Description	Commercial receptacles
Туре	Standard Duplex
Packaging Carton	10

Uses, Certifications, and Standards

Weight Per each

Application	Commercial Specification Grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-20R
standard	Certified to CSA 22.2, No. 42; Fed. Spec. W-C-596; NEMA® WD-6
	Compliant; UL Listed to UL498 File No. E2186