

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service Fax: 936-560-

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BR250SUR Type BR Surge & BRKR 50A/2 Pole 120/240V 10K Eaton Corp

Catalog Number	BR250SUR
Manufacturer	Eaton Corp
Description	Eaton BR Residential Surge Breaker, Two-Pole, 50A, 10 Ka Nominal Discharge, 36 Ka Surge Current
Weight per unit	2.0 (lbs/each)
Product Category	2 Pole Standard Trip Plug-In
Features	
amperage rating	50
Dimensions and Weight	
Height	3.5
Length	
Width	2.25
Descriptions	
Description	TYPE BR SURGE & BRKR 50A/2 POLE 120/240V 10K
extra long description	ETN BR250SUR BR SURGE & BRKR 50A/2
Features	Eaton offers a comprehensive family of surge products for use at service entrances. These products can help protect sensitive electronics against the damaging effects of surges. Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors t
Long Description	Eaton BR residential surge breaker, Two-pole, 50A, 10 kA nominal discharge, 36 kA surge current
Product Type	BR Surge & BRKR 50A/2 Pole 120/240V 10K
Manufacturer Information	
Brand	Eaton
GTIN	00786685546087
Manufacturers Part Number	BR250SUR
UPC	786685546087
Taxonomies, Classifications, and C Category Description	
Туре	
Packaging	
Carton	1
Weight Per each	2



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Datacenters - IT Space: CI and Hyper ConvergedOtherGeneration
	- Conventional Energy - Conventional EnergyMarine Vessels and
	Equipment - Marine Vessels and Equipment - OtherGeneration -
	Renewable Energy - Alternative Energy
standard	UL 1449,UL 489