

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

BR380 Type BR BRKR 80A/3 Pole 240V 10K Eaton Corp	
Catalog Number	BR380
Manufacturer	Eaton Corp
Description	Eaton BR Thermal Magnetic Circuit Breaker, Type BR 1-Inch Plug-On Circuit Breaker, 80 A, 10 Kaic, Three-Pole, 240V, BR, Common Breaker Trip, #4-1/0 Awg Cu/AI, Q28, BR, Type BR Loadcenters
Weight per unit	1.0 (lbs/each)
Product Category	3 Pole Standard Trip Plug-In
eatures	
dimensions	2.9000 IN X 2.9000 IN X 2.7000 IN
interrupt rating	10
Poles	3
Voltage Rating	240 V - 240 V
Descriptions	
Description	TYPE BR BRKR 80A/3 POLE 240V 10K
extra long description	ETN BR380 Type BR Breaker 80A/3 Pol
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton BR thermal magnetic circuit breaker,Type BR 1-Inch plug-on circuit breaker,80 A,10 kAIC,Three-pole,240V,BR,Common breaker trip,#4-1/0 AWG Cu/AI,Q28,BR,Type BR Loadcenters
Product Type	Type BR Breaker 80A/3 Pole 240V 10K
Manufacturer Information	
Brand	Eaton
GTIN	00782114103098
Manufacturers Part Number	BR380
UPC	782114103098
axonomies, Classifications, and (	Categories
Category Description	
Туре	Thermal magnetic circuit breakers
Packaging	
Carton	



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

standard

Generation - Renewable Energy - Alternative EnergyMarine Vessels and Equipment - Marine Vessels and Equipment -OtherOtherGeneration - Conventional Energy - Conventional EnergyDatacenters - IT Space: CI and Hyper Converged UL 489,Federal Specifications Classification W-C375