3000K



Project: Type: Prepared By: Date:



Features and Benefits

Energy efficient replacement for incandescent and halogen reflector lamps

Constructed from durable plastic which lowers risk of breakage

Rated for use in enclosed and open fixtures in dry or damp locations

Frosted lens produces smooth diffuse light

 $Longer\,life span\,compared\,to\,legacy\,equivalents\,minimizes\,replacement\,and\,maintenance\,costs$

ENERGY STAR Compliant

Dimmable with common dimmer types (see Dimmer Compatibility List)

Mercury and UV free. RoHS-compliant components.

Complies with Part 15B of the FCC Rules

FCC:

Performance	Electrical	Installation
Product Type:	Power Factor:	Base Type:
Reflector	>0.9	E26 Edison
Input Wattage:	Dimmable:	Optical
13W	Yes, down to 20%	Beam Angle:
		110°
Lumens:	Input Voltage:	
950lm	120V	Other
		Technology EQ:
Efficacy:	Operating Temperature:	Incandescent
73lm/W	-20°C to 40°C	
L70 Lifespan:	Construction	Compliance
25,000-Hour LED lifespan based on IES LM-70 results		UL Listed:
25,000 Hour EED mespan based of les EM 70 results	Bulb Shape: BR40	Yes
Wattage Equivalency:	DN40	
75W	Enclosure Material:	Environment:
	Plastic	Damp / Enclosed
LED Characteristics	i idatic	
Color Accuracy (CRI):	Housing Finish:	Energy Star ID:
80	White	2329453
Color Temperature:	Lens Finish:	Rohs:
	Lens Fillisti:	Mercury and UV free, RoHS-com

Frosted

BR40-13-830-DIM





Technical Specifications (continued)

Certification Model Number:

BR40-13-830-DIM

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	6	15.8	10.6	7
PALLET	360	47.2	37	34.8



