

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BRCAF120CS Eaton BR Afci Circuit Bre Eaton Corp

Catalog Number	BRCAF120CS
Manufacturer	Eaton Corp
Description	Eaton BR Afci Circuit Breaker, Afci Circuit Breaker, Clamshell
	Pack, 20 A, 10 Kaic, Single-Pole, 120 V, BRC, Pigtail, #14-4 Awg
	Cu/Al, Q30, Type BR Loadcenters
Weight per unit	0.4500 (lbs/each)
Product Category	In Circuit Breakers

Features

connection	Pigtail
dimensions	6.0000 IN X 3.5000 IN X 1.2500 IN
interrupt rating	10
Poles	1
Voltage Rating	120 V

Descriptions

Description	EATON BR AFCI CIRCUIT BRE
extra long description	ETN BRCAF120CS BR COMBINATION AFCI,
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton BR AFCI circuit breaker, AFCI Circuit breaker, Clamshell pack, 20 A, 10 kAIC, Single-pole, 120 V, BRC, Pigtail, #14-4 AWG Cu/AI, Q30, Type BR Loadcenters
Product Type	BR Combination Afci, 1P, 20A, 10KAIC,
Special Features	Clamshell pack

Manufacturer Information

Brand	Eaton	
GTIN	00786685514376	
Manufacturers Part Number	BRCAF120CS	
UPC	786685514376	

Taxonomies, Classifications, and Categories

Category Description	Loadcenter Plug In Breakers and Accessories
Туре	AFCI circuit breakers



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	0.45
Uses, Certifications, and Standa	ards
Application	Generation - Conventional Energy - Conventional
	EnergyOtherMarine Vessels and Equipment - Marine Vessels and
	Equipment - OtherGeneration - Renewable Energy - Alternative
	EnergyDatacenters - IT Space: CI and Hyper Converged
standard	UL 1699, Federal Specifications Classification W-C375