

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

BT1.5IC 6" Nyln CBL Tie SS Barb Int Cross Sec WHT Panduit Corporation

Catalog Number	BT1.5IC
Manufacturer	Panduit Corporation
Description	The BT1.5I-C Dome-Top® Barb Ty, Features A Unique Patented Design With Its Round Smooth Edges. Paired With The Stainless-Steel Locking Barb, These Cable Ties Provide Consistent Performance, Reliability and Infinite Adjustability Through The Entire Bundle Range. Intermediate Cross Section, 6.1" (155MM) Length. Appropriate For Indoor Use, Made Of Nylon 6.6, Are Natural In Color and Come In Packages Of 100.
Weight per unit	0.2000 (lbs/each)
Product Category	Cable Ties & Wraps
Features	·
media	Yes
Tensile Strength	40
Dimensions and Weight	
Length	6.1
Thickness	0.04
Descriptions	
Description	6" NYLN CBL TIE SS BARB INT CROSS SEC WHT
extra long description	PAN BT1.5I-C Dome-Top® BT1.5I-C Bar
Long Description	The BT1.5I-C Dome-Top® barb ty, features a unique patented
	design with its round smooth edges. Paired with the
	stainless-steel locking barb, these cable ties provide consistent performance, reliability and infinite adjustability through the
	entire bundle range. Intermediate cross section, 6.1" (155mm) length. Appropriate for Indoor use, made of Nylon 6.6, are natural in color and come in packages of 100.
Product Type	Dome-Top® BT1.5I-C Barb Tie, PA6.6, 6.1"L, 40LB, PK100
Special Features	Indoor
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983413331
Manufacturers Part Number	BT1.5I-C
UPC	074983413331
Taxonomies, Classifications, and (Categories
Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
	· · · · · ·

Cable Tie



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability minimum qty	100
Packaging Carton	100
Package	1000
Weight Per each	0.2
Uses, Certifications, and Standards	
standard	UL 62275 (File E56854), CSA-C22.2 No. 62275, 11130200, NRC
	10CFR50, QPL-AS23190, CSA Certified, RoHS Compliant