

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

BT2SC 8" NyIn CBL Tie SS Barb STD Cross Sec WHT Panduit Corporation



Catalog Number	BT2SC
Manufacturer	Panduit Corporation
Description	The BT2S-C Dome-Top [®] Barb Ty, Features A Unique Patented Design With Its Round Smooth Edges. Paired With The Stainless-Steel Locking Barb, These Cable Ties Provide Consisten Performance, Reliability and Infinite Adjustability Through The Entire Bundle Range. Standard Cross Section, 8.0" (203MM) Length. Appropriate For Indoor Use, Made Of Nylon 6.6, Are Natural In Color and Come In Packages Of 100.
Weight per unit	0.3510 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
media	Yes
Tensile Strength	
Dimensions and Weight	
Length	
Thickness	0.05
Descriptions	
Description	8" NYLN CBL TIE SS BARB STD CROSS SEC WHT
extra long description	PAN BT2S-C Dome-Top [®] BT2S-C Barb Ti
Long Description	The BT2S-C Dome-Top [®] barb ty, features a unique patented design with its round smooth edges. Paired with the stainless-steel locking barb, these cable ties provide consistent performance, reliability and infinite adjustability through the entire bundle range. Standard cross section, 8.0" (203mm) length. Appropriate for Indoor use, made of Nylon 6.6, are natural in color and come in packages of 100.
Product Type	Dome-Top® BT2S-C Barb Tie, PA6.6, 8"L, 50LB, PK100
Special Features	Indoor
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983411764
Manufacturers Part Number	BT2S-C
UPC	074983411764



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Туре	Cable Tie
Availability	
minimum qty	100
Packaging	
Carton	100
Package	1000
Weight Per each	0.351
Uses, Certifications, and Standards	
	LU (0075 (FIL FE(0E4) 004 000 0 NL (0075 11100000 ND0

standard	UL 62275 (File E56854), CSA-C22.2 No. 62275, 11130200, NRC
	10CFR50, QPL-AS23190, CSA Certified, RoHS Compliant