

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BT3LHL0 Nylon Cable Tie *Panduit Corporation*

100	
Catalog Number	BT3LHL0
Manufacturer	Panduit Corporation
Description	The BT3LH-LO Dome-Top® Barb Ty, Features A Unique Patented Design With Its Round Smooth Edges. Paired With The Stainless-Steel Locking Barb, These Cable Ties Provide Consistent Performance, Reliability and Infinite Adjustability Through The Entire Bundle Range. Light-Heavy Cross Section, 11.8" (300MM) Length. Appropriate For Indoor/Outdoor Use, Made Of Weather Resistant Nylon 6.6 With High Resistance to Ultraviolet Light, Are Black In Color and Come In Packages Of 50.
Weight per unit	0.5970 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
media	Yes
Tensile Strength	120
Dimensions and Weight	
Length	11.8
Thickness	0.07
Descriptions	
Description	NYLON CABLE TIE
extra long description	PAN BT3LH-L0 Dome-Top® BT3LH-L0 Bar
Long Description	The BT3LH-L0 Dome-Top® barb ty, features a unique patented design with its round smooth edges. Paired with the stainless-steel locking barb, these cable ties provide consistent performance, reliability and infinite adjustability through the entire bundle range. Light-Heavy cross section, 11.8" (300mm) length. Appropriate for Indoor/Outdoor use, made of Weather Resistant Nylon 6.6 with high resistance to ultraviolet light, are black in color and come in packages of 50.
Product Type	Dome-Top® BT3LH-L0 Barb Tie, Black, Uv PA6.6, 11.8"L, 120LB,
Special Features	Indoor/Outdoor
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983412631
Manufacturers Part Number	BT3LH-L0
UPC	074983412631



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Туре	Cable Tie
Packaging	
Carton	50
Package	500
Weight Per each	0.597

Uses, Certifications, and Standards

standard	UL 62275 (File E56854), CSA-C22.2 No. 62275, 11130200, NRC
	10CFR50, QPL-AS23190, CSA Certified, RoHS Compliant