

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



C1.5BL6 1-1/2 Black CVR P/FT

Panduit Corporation

意味を入る	
Catalog Number	C1.5BL6
Manufacturer	Panduit Corporation
Description	The C1.5BL6 PVC Flush Wiring Duct Cover Features A Non-Slip,
	Liner to Prevent Cover Slide. Designed With The User In Mind,
	The Cover Is Easy to Install and Remove. The General-Purpose
	Lead-Free PVC Material Is Suitable For Use In Indoor Application
	UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use
	Temperature Up to 122°F (50°C). 0.35" X 1.75" (8.9 MM X 44.5
Woight por unit	MM) and 6' (1.83 M) Long. Color Black. 0.5300 (lbs/each)
Weight per unit	,
Product Category	Ducts, Raceways, Runways, Tray
eatures	
connection	Snap-on
media	Yes
Material, Color, and Finish	
Color	Black
Dimensions and Weight	
Length	NA
Width	1.75
Descriptions	
Description	1-1/2 BLACK CVR P/FT
extra long description	PAN C1.5BL6 Panduct® C1.5BL6 Flush
Long Description	The C1.5BL6 PVC Flush Wiring Duct Cover features a non-slip,
	liner to prevent cover slide. Designed with the user in mind, the
	cover is easy to install and remove. The general-purpose
	lead-free PVC material is suitable for use in indoor applications.
	UL 94 flame class of V-0 with a UL recognized continuous-use
	temperature up to 122°F (50°C). 0.35" x 1.75" (8.9 mm x 44.5
	mm) and 6' (1.83 m) long. Color Black.
Product Type	Panduct® C1.5BL6 Flush Duct Cover
Vlanufacturer Information	
Brand	PANDUIT
GTIN	00074983230594
Manufacturers Part Number	C1.5BL6
UPC	074983230594



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	WIRE DUCT AND COVERS	
Туре	Flushed Duct Cover	
Packaging		
Carton	120	
Weight Per each	0.53	
Uses, Certifications, and Standa	rds	
Application	Cover for Wiring Duct	
standard	CE Compliant; CSA Certified; Flammability Ratings: UL94 V-0; RoHS	
	Compliant;UL Recognized	