

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



C25DND330C Open N-R 3P 30A DP Cont SCR/PP W/QC Term 480VAC CO Eaton Corp

TOTAL	
Catalog Number	C25DND330C
Manufacturer	Eaton Corp
Description	Eaton Definite Purpose Contactor, Quick, 30A, 440-480 Vac, 50/60 HZ, Open With Metal Mounting Plate, 15-50A, Two- and Three-Pole, 30A, Contactor, Three-Pole, 40A, Screw/Pressure Plate and Quick Connect Terminals (Side-By-Side), Non-Reversing
Weight per unit	1.2 (lbs/each)
Product Category	Definite Purpose Contactors
Features	
Enclosure Type	Open with metal mounting plate
induct amp/res amp rating	30/40
Voltage Rating	480
Dimensions and Weight	
Depth	3.35
Height	3.6
Width	2.4
Descriptions	
Description	OPEN N-R 3P 30A DP CONT SCR/PP W/QC TERM 480VAC CO
extra long description	ETN C25DND330C OP N-R 3P 30ADPCNT S
Features	Definite purpose contactors and starters are electrically operated switching devices specifically designed for the heating, ventilation, air conditioning and refrigeration (HVAC) industry.
Long Description	Eaton definite purpose contactor, Quick, 30A, 440-480 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 30A, Contactor, Three-pole, 40A, Screw/pressure plate and quick connect terminals (side-by-side), Non-reversing
Product Type	Op N-R 3P 30ADPCNT SCR/PP W/QC480VCL
Manufacturer Information	
Brand	EATON CUTLER-HAMMER
GTIN	00782116308859
Manufacturers Part Number	C25DND330C
UPC	782116308859
Taxonomies, Classifications, and Category Description	DD CONTACTORS
Type	
: J PY	Bollinto par pose contractor



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	1.19
Uses, Certifications, and Standards	
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
standard	CSA Certified, UL Recognized, RoHS Compliant