

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## C6 #6 Cu Long Barrel Compression Butt Splice

Nsi Industries	rrei Compression Butt Spilce
Catalog Number	C6
Manufacturer	Nsi Industries
Description	Compression Splice Connector, #8 Awg Conductor Size, #6 Awg Conductor Size, Non-Insulated, Copper Conductor Material, Blue Insulation Color, 2 Conductors, +90 °C Operating Temperature, 1.752 In Overall Length, Compression Terminal, 600 V, 0.04 LB/Ea
Weight per unit	0.0400 (lbs/cash)
Product Category	Large Terminals & Connectors
Features	
Material	Copper
Number of Conductors	2
Poles	1
Voltage Rating	
Warranty	1 VEAD
Material, Color, and Finish	
Color	Blue
Finish	Tin Plated
<b>Dimensions and Weight</b>	
Size	L=1.75 - OD=.300 - ID=.200
<b>Descriptions</b>	#6 CU LONG BARREL COMPRESSION BUTT SPLICE
Description extra long description	NSI C-6 6 AWG Copper Long Barrel Sp
Features	Long Barrel TinnedCopperSplice6 AWG Long Barrel Tinned
reatures	CopperSplices is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Manufacturer Information	
GTIN	00662381037503
UPC	662381037503
Taxonomies, Classifications, and	Categories
Category Description	Common O. March Lung and Dutt College
Type	
Packaging	
Carton	1
Package	100
M. '.l. Dl.	0.04

0.04

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486A/B, UL467 (8 AWG -3/0 AWG)
Temperature Rating	90 C