

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



C75M 3/4" C FM5 Conduit Body Crouse-Hinds

| Catalog Number | C75M |
|------------------|---|
| Manufacturer | Crouse-Hinds |
| Description | Conduit Body, Electrogalvanized With Aluminum Acrylic Paint, Form 5 Body Type, 3/4 In Trade Size, Threaded Connection, C Shape, Side Cable Entry, 2 Hubs, 3/4 In Hub Size, Straight Hub Location, C Configuration, 6 In Length, 1.5 In Width, 1.7 In Height, Threaded, 0.99 LB/Ea |
| Weight per unit | 0.9900 (lbs/each) |
| Product Category | Bodies & Covers |

Features

| dimensions | 6.0000 IN X 1.5000 IN X 1.7000 IN |
|------------|-----------------------------------|
| Form | Form 5 |

Dimensions and Weight

| Height | 1.70 |
|--------|------|
| Length | 6.00 |

Descriptions

| Description | 3/4" C FM5 CONDUIT BODY |
|------------------------|---|
| extra long description | CRS-H C75M 3/4 FORM 5 C COND BODY M |
| Features | Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h |
| | AIST AVAIIATIE WITT A IT |

Manufacturer Information

| Brand | Eaton |
|-------|----------------|
| GTIN | 00782274756349 |
| UPC | 782274756349 |

Taxonomies, Classifications, and Categories

| Category Description | FORM 5 CONDULETS, COVERS, & GASKETS |
|----------------------|-------------------------------------|
| Туре | Conduit outlet body |

Packaging

| Carton | 10 |
|-----------------|------|
| Weight Per each | 0.99 |

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Uses, Certificat | tions, and | l Stand | ards |
|------------------|------------|---------|------|
|------------------|------------|---------|------|

standard UL 514B, CSA C22.2, CUL