

## UNION® BOX CEILING FAN and FIXTURE BOX MOUNTING INSTRUCTIONS FOR CATALOG NUMBERS

CFB-12, CFB-16, CFB-16F, CFBSO-612, CFBSO-858, CFB-612 and CFB-858



### WARNING



**FAN MOUNTING SCREWS, FURNISHED  
WITH CEILING BOX, MUST BE USED.**

### INSTRUCTIONS:

- 1) Position and press box on joist.
- 2) Fasten #12 x 5/8" preinstalled screw near center of box.  
**NOT REQUIRED FOR CFBSO-612 and CFBSO-858.**
- 3) Drill 1/8" diameter pilot holes through the two oval slots.
- 4) Pull out the two #12 x 2" long screws, and use them to install Fan or Fixture bracket through oval slots, into drilled holes.
- 5) Mount Fan or Fixture and make the electrical connections in accordance with local electrical codes and instructions provided with Fan or Fixture.

**WARRANTY:** Thomas & Betts sells this product with the understanding that the user will perform all necessary tests to determine the suitability of this product for the user's intended application. Thomas & Betts warrants that this product will be free from defects in materials or workmanship for a period of two (2) years following the date of purchase. Upon prompt notification of any warranted defect, Thomas & Betts will, at its option, repair or replace the defective product. Misuse, misapplication or modification of Thomas & Betts Products immediately voids all warranties.

Limitations and Exclusions: **THE ABOVE WARRANTY IS THE SOLE WARRANTY CONCERNING THIS PRODUCT, AND IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE SPECIFICALLY DISCLAIMED. LIABILITY FOR BREACH OF THE ABOVE WARRANTY IS LIMITED TO COST OF REPAIR OR REPLACEMENT OF THE PRODUCT, AND UNDER NO CIRCUMSTANCES WILL THOMAS & BETTS BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

## UNION® BOX CEILING FAN and FIXTURE BOX MOUNTING INSTRUCTIONS FOR CATALOG NUMBERS

CFB-12, CFB-16, CFB-16F, CFBSO-612, CFBSO-858, CFB-612 and CFB-858



### WARNING



**FAN MOUNTING SCREWS, FURNISHED  
WITH CEILING BOX, MUST BE USED.**

### INSTRUCTIONS:

- 1) Position and press box on joist.
- 2) Fasten #12 x 5/8" preinstalled screw near center of box.  
**NOT REQUIRED FOR CFBSO-612 and CFBSO-858.**
- 3) Drill 1/8" diameter pilot holes through the two oval slots.
- 4) Pull out the two #12 x 2" long screws, and use them to install Fan or Fixture bracket through oval slots, into drilled holes.
- 5) Mount Fan or Fixture and make the electrical connections in accordance with local electrical codes and instructions provided with Fan or Fixture.

**WARRANTY:** Thomas & Betts sells this product with the understanding that the user will perform all necessary tests to determine the suitability of this product for the user's intended application. Thomas & Betts warrants that this product will be free from defects in materials or workmanship for a period of two (2) years following the date of purchase. Upon prompt notification of any warranted defect, Thomas & Betts will, at its option, repair or replace the defective product. Misuse, misapplication or modification of Thomas & Betts Products immediately voids all warranties.

Limitations and Exclusions: **THE ABOVE WARRANTY IS THE SOLE WARRANTY CONCERNING THIS PRODUCT, AND IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE SPECIFICALLY DISCLAIMED. LIABILITY FOR BREACH OF THE ABOVE WARRANTY IS LIMITED TO COST OF REPAIR OR REPLACEMENT OF THE PRODUCT, AND UNDER NO CIRCUMSTANCES WILL THOMAS & BETTS BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**