

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Product Type

Special Features

# CH24L225R 1PH/CH Loadcenter 225A Mlo 24 Cir. Cu Bus Nema 3R Eaton Corp

Catalog Number	CH24L225R
Manufacturer	Eaton Corp
Description	Eaton CH Main Lug Loadcenters, Standard, Main Lug Only, 225A, D, Copper, Nema 3R, Metallic, Overhead, CH, 24, 24, Three-Wire, Single-Phase, 120/240 V, #4 Awg-300 Kcmil
Weight per unit	29.0 (lbs/each)
Product Category	Single Phase Main Lug Load Cen
Features	
amperage rating	225
number of spaces	24
Phase	1
Voltage Rating	120/240 V
<b>Dimensions and Weight</b>	
Depth	21
Height	5.19
Size	D
Width	14.31
Descriptions	
Description	1PH/CH LOADCENTER 225A MLO 24 CIR. CU BUS NEMA 3R
extra long description	ETN CH24L225R Eaton CH main lug loa
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH main lug loadcenters, Standard, Main lug only, 225A, D, Copper, NEMA 3R, Metallic, Overhead, CH, 24, 24, Three-wire, Single-phase, 120/240 V, #4 AWG-300 kcmil
5 · · <del>-</del>	

Standard

Eaton CH Main Lug Loadcenter



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Λ	/lani	ıfactı	ırer	Inforr	nation
II.	viaii	นเสเเน	ai ei		nauwn

Brand	EATON CUTLER-HAMMER
GTIN	00782113097749
Manufacturers Part Number	CH24L225R
UPC	782113097749

## **Taxonomies, Classifications, and Categories**

Category Description	LOADCENTERS & COVERS
Type	Main lug loadcenter

### **Availability**

•	
Status	Inactive

### **Packaging**

onaging		
Carton	1	
Weight Per each	29	

#### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
standard	UL 67,UL 50