Specifications



Eaton CHCC3DIU

Eaton Bussmann series CHCC modular fuse holder, 48 Vdc, 30 A, Three-pole, With indicator

| General specifications | |
|-------------------------|---|
| PRODUCT NAME | Eaton Bussmann series CHCC modular fuse holder |
| CATALOG NUMBER | CHCC3DIU |
| UPC | 051712362702 |
| PRODUCT LENGTH/DEPTH | 2.7 in |
| PRODUCT HEIGHT | 2.91 in |
| PRODUCT WIDTH | 3.28 in |
| PRODUCT WEIGHT | 0.3875 lb |
| WARRANTY | Not Applicable |
| COMPLIANCES | RoHS Compliant |
| CERTIFICATIONS | Contact Manufacturer |



| Electrical rating | |
|-------------------|--------|
| AMPERAGE RATING | 30 A |
| VOLTAGE RATING | 48 Vdc |

| Physical details | |
|--------------------------------|------------|
| NUMBER OF POLES | Three-pole |
| OPERATING TEMPERATURE - MAX | 90 °C |
| OPERATING TEMPERATURE - MIN | -20 °C |

| General information | |
|---------------------|--|
| CLASS | Class CC |
| USED WITH | For use with KTK-R, LP-CC and FNQ-R Class CC fuse |

| Resources | |
|-------------------------------|---|
| CATALOGS | CHCC3DIU~ |
| | Bussmann series complete full line catalog no. 1007 |
| CERTIFICATION REPORTS | Eaton Bussmann EU Declaration of conformity 93-68-EEC2308-B |
| MULTIMEDIA | Bussmann series Fuseology |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - CHCC3DIU |
| TECHNICAL DATA SHEETS | 720147 10 x 38 mm Modular fuse holder |

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

D 1

Follow us on social media to get the latest product and support information.











Specifications



Eaton CHCC3DIU

Eaton Bussmann series CHCC modular fuse holder, 48 Vdc, 30 A, Three-pole, With indicator

| General specifications | |
|-------------------------|---|
| PRODUCT NAME | Eaton Bussmann series CHCC modular fuse holder |
| CATALOG NUMBER | CHCC3DIU |
| UPC | 051712362702 |
| PRODUCT LENGTH/DEPTH | 2.7 in |
| PRODUCT HEIGHT | 2.91 in |
| PRODUCT WIDTH | 3.28 in |
| PRODUCT WEIGHT | 0.3875 lb |
| WARRANTY | Not Applicable |
| COMPLIANCES | RoHS Compliant |
| CERTIFICATIONS | Contact Manufacturer |



| Electrical rating | |
|-------------------|--------|
| AMPERAGE RATING | 30 A |
| VOLTAGE RATING | 48 Vdc |

| Physical details | |
|--------------------------------|------------|
| NUMBER OF POLES | Three-pole |
| OPERATING TEMPERATURE - MAX | 90 °C |
| OPERATING TEMPERATURE - MIN | -20 °C |

| General information | |
|---------------------|--|
| CLASS | Class CC |
| USED WITH | For use with KTK-R, LP-CC and FNQ-R Class CC fuse |

| Resources | |
|-------------------------------|---|
| CATALOGS | CHCC3DIU~ |
| | Bussmann series complete full line catalog no. 1007 |
| CERTIFICATION REPORTS | Eaton Bussmann EU Declaration of conformity 93-68-EEC2308-B |
| MULTIMEDIA | Bussmann series Fuseology |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - CHCC3DIU |
| TECHNICAL DATA SHEETS | 720147 10 x 38 mm Modular fuse holder |

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

D 1

Follow us on social media to get the latest product and support information.









