Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

CHN215GF CH 5MA Gfci 2P 15A 120/240V 10kaic
Eaton Corp

Catalog Number	CHN215GF
Manufacturer	Eaton Corp
Description	Eaton CH Gfci Circuit Breaker, Plug-In Circuit Breaker, 15 A, 10 Kaic, Two-Pole, 120/240 V, CH, Common, GFI, 5 Ma
Weight per unit	0.8000 (lbs/each)
Product Category	In Circuit Breakers

Features

dimensions	6.0000 IN X 3.5000 IN X 2.2500 IN
interrupt rating	10
Poles	2
Voltage Rating	120/240 V

Descriptions

Description	CH 5MA GFCI 2P 15A 120/240V 10KAIC
extra long description	ETN CHN215GF CH 5mA GFCI, 2P, 15A,
Features	Eaton's residential CH circuit breakers provide premium overload protection. The Type CH circuit breakers trip to the OFF position, eliminating nuisance callbacks. The CHF family also includes a trip flag to differentiate between a trip and the breaker being turned off. The thermal-magnetic trip curve avoids nuisance tripping on mild overloads while reacting almost instantaneously to severe short-circuit conditions. Multiple breakers have an internal common trip connection to operate all poles simultaneous
Long Description	Eaton CH GFCI circuit breaker,Plug-in circuit breaker,15 A,10 kAIC,Two-pole,120/240 V,CH,Common,GFI,5 mA
Product Type	CH 5MA Gfci, 2P, 15A, 120/240V, 10kaic

Manufacturer Information

Brand	Eaton
GTIN	00786689217211
Manufacturers Part Number	CHN215GF
UPC	786689217211

Taxonomies, Classifications, and Categories

Type	GFCI circuit breakers

Packaging

Carton	1
Weight Per each	0.8

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application	OtherGeneration - Renewable Energy - Alternative EnergyGeneration - Conventional Energy - Conventional EnergyMarine Vessels and Equipment - Marine Vessels and Equipment - OtherDatacenters - IT Space: CI and Hyper Converged
standard	UL 489