Eaton CHR8N8N5NS

Catalog Number: CHR8N8N5NS

Eaton pedestal mount metered, Pos 1: Non-gnd fault, Pos 2: Non-gnd fault, Pos 3: Non-gnd fault, Circuits: 4, 1, Weather-resist center and left receptacle, Center: NEMA 5-20R2GFI WR, Left: NEMA 5-20R2GFI WR, Right: NEMA 6-20R2, Ringless

General specifications



Eaton pedestal mount metered

UPC

786685948461

Product Height

8 in

Product Weight

24 lb

Catalog Number

CHR8N8N5NS

Product Length/Depth

31 in

Product Width

10 in

Warranty

Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Photo is representative

Certifications

UL Listed



Product specifications

Type

Metered-ringless

Utility approvals

IA: Alliant (IP&L and WP&L)
WI: Alliant (IP&L and WP&L)

FL: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

IN: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

KY: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

NC: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

OH: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

SC: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

FL: Tallahassee City Electric

Receptacle center

5-20R2GFI WR

Receptacle left

5-20R2GFI WR

Receptacle right

6-20R2

Feed type

Top

Number of circuits

4

Number of sockets

1

Resources

Specifications and datasheets

Eaton Specification Sheet - CHR8N8N5NS



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2025 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia